JAD047303721

Page 48 redacted per exemption 6 - PII

DOCUMENTATION OF ENVIRONMENTAL INDICATOR DETERMINATION

Interim Final 2/5/99 Revised 9/20/02

RCRA Corrective Action Environmental Indicator (EI) RCRA Info code (CA725) Current Human Exposures Under Control

Facility Name:	Collis Inc.	
Facility Address:	2005 S. 19th Street, Clinton, IA 52732	
Facility EPA ID #:	IAD047303771	

DETERMINATION RESULT: YE

1.	groundwater, sur	face water/sediments, and air, subject to RCRA Corrective Action (e.g., from Solid Waste its (SWMU), Regulated Units (RU), and Areas of Concern (AOC)), been considered in tion?
	X	If yes - check here and continue with #2 below.
	-	If no - re-evaluate existing data, or
		if data are not available skip to #6 and enter"IN" (more information needed) status code.
		acility is located on about 12.5 acres in Clinton, Iowa (see Figure 1). The facility has gone ership changes since it was opened by Collis in 1915, but it is now a division of SSW

The Collis, Inc. (Collis) facility is located on about 12.5 acres in Clinton, Iowa (see Figure 1). The facility has gone through a number of ownership changes since it was opened by Collis in 1915, but it is now a division of SSW Enterprises, Inc., which acquired Collis in 1998 (Heritage Environmental Services [Heritage] 2000a). Collis began in 1915 by manufacturing wire products, prefabricated buildings, and other metal agricultural parts. In 1964, the facility switched to manufacture of refrigerator parts, including wire racks, shelves, and other accessories (Heritage 2000a; U.S. Environmental Protection Agency [EPA] 2001). In the past, Collis's manufacturing processes included zinc-cyanide and nickel-chromium plating, but it has converted all its current operations to zinc-chloride plating and epoxy-powder coating (Heritage 2000a). Collis has also operated a wastewater treatment plant (WWTP) since 1970. From 1970 until 1979, sludges from the wastewater treatment plant were directed to surface impoundments. After 1979, sludges were landfilled offsite (Heritage 2000a). The facility continues to discharge wastewater to Manufacturers Ditch under a National Pollutant Discharge Elimination System (NPDES) permit (Heritage 2000a). The facility now generates less than 100 kilograms of hazardous waste per month (EPA 2001).

The Collis facility has been monitored and investigated since at least 1986, when the facility closed the surface impoundments. The closure process continued from 1986 to 1993, when the facility entered into an Administrative Order on Consent (AOC) with EPA. The AOC required the facility to conduct a Resource Conservation and Recovery Act (RCRA) facility investigation (RFI) to determine the nature and extent of releases from seven solid-waste management units (SWMU) at the facility (Heritage 2000a) (see Figure 2). Investigations of groundwater, soil, sediment, and surface water contamination continued through the 1990s, with the RFI completed in 1998 (Heritage 1998a). Additional investigations were conducted in 2000 (Heritage 2000b).

The primary contaminants released to soil, groundwater, sediment, and surface water from Collis's SWMUs are metals derived from the plating process (especially chromium, nickel, and zinc); chlorinated and petroleum-derived volatile organic compounds (VOC); and polycyclic aromatic hydrocarbon (PAH) semivolatile organic compounds (SVOC) (Heritage 2000a). Polychlorinated biphenyls (PCB) also have been detected in a limited number of locations at the facility (Heritage 1998a).



SWMU 1 - Floor Drain, Sump, and Overhead Pipe System (FDS). SWMU 1 includes the plating lines and other equipment used to channel waste to the WWTP, including spent caustics, rinse water, spent pickle solutions, and spent metal solutions (Heritage 1994). It was built in 1970, and the lines are still in use, although the wastes are no longer hazardous (Heritage 1994). Metals have been detected in subsurface soil and groundwater from the area of this SWMU (Heritage 2000a).

SWMU 2 - Pollution Control Building (PCA). SWMU 2 is the location of the process wastewater system and WWTP, consisting of several concrete underground storage tanks (UST) and two aboveground storage tanks for the batch treatment of chromate solutions, spent acid, and caustic soda solution (Heritage 1994). It was constructed in 1970 and is still in use. Metals have been detected in surface and subsurface soils, and VOCs have been detected in surface soils and groundwater at this SWMU (Heritage 1998a, 2000a).

SWMU 3 - Sludge Management Area (SMA). SWMU 3 includes the solids settling tank and sludge filter press operations that are used to process and dewater sludge from the WWTP (Heritage 1994). The WWTP was constructed in 1970 and is still used today, although sludges are now disposed of offsite (Heritage 1994). The settling basin occasionally has overflowed, and inspections of the WWTP by Iowa Department of Environmental Quality have documented several instances of poorly stored chemicals in SWMU 3 (Heritage 1994). Metals have been detected in surface soils, and VOCs have been detected in subsurface soils and groundwater at this SWMU (Heritage 2000a).

SWMU 4 - Sludge Impoundment Area (SIA). SWMU 4 includes the area of the former sludge impoundments, which were built in 1970 as part of the WWTP and received sludge until 1979 (Heritage 1994). Sludges are now sent to an offsite landfill (Heritage 1994). The SIA impoundments were excavated to a depth of about 3 to 4 feet below grade but were not lined (Heritage 1994). In some cases, the bottom of the impoundment was at the water table (Heritage 1994). Although the number of impoundments varied, with as many as seven impoundments for hazardous waste (sludges) before 1980, there were five impoundments in 1980 when the facility began the closure process (Heritage 1994). The facility conducted closure activities (excavation and investigation) from 1986 to 1990, but the facility never received a clean-closure certification (Heritage 2000a). The area is now grass covered, and the impoundments were filled with a variety of materials, including organic matter, clay, cinders, bricks, glass fragments, metal shavings, and gravel (Heritage 1998a). Metals have been detected in surface and subsurface soils. PCBs, VOCs, and SVOCs have been detected in surface soil (Heritage 2000a). VOCs have also been detected in groundwater (Heritage 1998a).

SWMU 5 - Closure Pretreatment Area (CPA). SWMU 5 was used only from 1986 to 1987 as an area to treat water generated during the closure of the sludge impoundments (Heritage 1994). It consisted of three 27-foot diameter swimming pool tanks and was dismantled in 1988 (Heritage 1994). Metals have been detected in surface soil, and VOCs have been detected in groundwater from the area of this SWMU (Heritage 2000a).

SWMU 6 - Northeast Yard and Receiving Dock, Outdoor Storage Yard (NEY). SWMU 6 is an area used for receiving, storing, and shipping products and waste (Heritage 2000a). It was also the location of a railroad spur (no longer in service) and a gasoline UST that was removed in 1988 (Heritage 1994, 1998b). The area currently is used to store empty drums, scrap metal, and waste oil (Heritage 1994). Metals, VOCs, SVOCs, and PCBs have been detected in surface and subsurface soil. VOCs have been detected in groundwater from the area of this SWMU (Heritage 1998a).

SWMU 7 - Manufacturers Ditch Area (MDA). SWMU 7 is the main stormwater drainage ditch for Collis and other industrial, residential, and agricultural stormwater runoff from upstream and downstream of the facility (Heritage 1998a). In 1992, the ditch was dredged and excavated by the city, and the materials were used as fill material at a nearby park (Heritage 1994). Metals and VOCs were detected in soil and sediment, and VOCs were detected in groundwater from this SWMU (Heritage 2000a). Surface water was not significantly contaminated.

BACKGROUND

Definition of Environmental Indicators (for the RCRA Corrective Action)

Environmental Indicators (EI) are measures being used by the RCRA Corrective Action program to go beyond programmatic activity measures (e.g., reports received and approved, etc.) to track changes in the quality of the environment. The two EI developed to-date indicate the quality of the environment in relation to current human exposures to contamination and the migration of contaminated groundwater. An EI for non-human (ecological) receptors is intended to be developed in the future.

Definition of "Current Human Exposures Under Control" EI

A positive "Current Human Exposures Under Control" EI determination ("YE" status code) indicates that there are no "unacceptable" human exposures to "contamination" (i.e., contaminants in concentrations in excess of appropriate risk-based levels) that can be reasonably expected under current land- and groundwater-use conditions (for all "contamination" subject to RCRA corrective action at or from the identified facility (i.e., site-wide)).

Relationship of EI to Final Remedies

While Final remedies remain the long-term objective of the RCRA Corrective Action program the EI are near-term objectives which are currently being used as Program measures for the Government Performance and Results Act of 1993, GPRA). The "Current Human Exposures Under Control" EI are for reasonably expected human exposures under current land- and groundwater-use conditions ONLY, and do not consider potential future land- or groundwater-use conditions or ecological receptors. The RCRA Corrective Action program's overall mission to protect human health and the environment requires that Final remedies address these issues (i.e., potential future human exposure scenarios, future land and groundwater uses, and ecological receptors).

Duration / Applicability of EI Determinations

EI Determinations status codes should remain in RCRA Info national database ONLY as long as they remain true (i.e., RCRA Info status codes must be changed when the regulatory authorities become aware of contrary information).

2. Are groundwater, soil, surface water, sediments, or air media known or reasonably suspected to be "contaminated" above appropriately protective risk-based "levels" (applicable promulgated standards, as well as other appropriate standards, guidelines, guidance, or criteria [e.g., Maximum Contaminant Levels (MCLs), the maximum permissible level of a contaminant in water delivered to any user of a public water system under the Safe Drinking Water Act] from releases subject to RCRA Corrective Action (from SWMUs, RUs, or AOCs)?

Media	Yes	No	?	Rationale/Key Contaminants
Groundwater	Х	Desire y		
Air (indoors) ²	х			
Surface Soil (e.g., <2 ft)	Х			
Surface Water		х		See below for details
Sediment	х			il.
Subsurf. Soil (e.g., >2 ft)	Х			
Air (outdoors)		х		

	If no (for all media) - skip to #6, and enter "YE," status code after providing or citing appropriate "levels," and referencing sufficient supporting documentation demonstrating that these "levels" are not exceeded.
X	If yes (for any media) - continue after identifying key contaminants in each "contaminated" medium, citing appropriate "levels" (or provide an explanation for the determination that the medium could pose an unacceptable risk), and referencing supporting documentation.
	If unknown (for any media) - skip to #6 and enter "IN" status code.

Rationale and Reference(s):

The Collis facility is located on about 12.5 acres in Clinton, Iowa, in an area that has been designated an industrial development zone by the city of Clinton (see Figure 1) (Heritage 2000a). The surrounding land is used for a mix of residential, agricultural, commercial, and light industrial activities (Heritage 2000a). The facility is bordered on the

¹ "Contamination" and "contaminated" describes media containing contaminants (in any form, NAPL and/or dissolved, vapors, or solids, that are subject to RCRA) in concentrations in excess of appropriately protective risk-based "levels" (for the media, that identify risks within the acceptable risk range).

²Recent evidence (from the Colorado Dept. of Public Health and Environment, and others) suggest that unacceptable indoor air concentrations are more common in structures above groundwater with volatile contaminants than previously believed. This is a rapidly developing field and reviewers are encouraged to look to the latest guidance for the appropriate methods and scale of demonstration necessary to be reasonably certain that indoor air (in structures located above (and adjacent to) groundwater with volatile contaminants) does not present unacceptable risks.

north by railroad tracks, on the north and west by Manufacturers Ditch, on the west by S. 19th Street, on the south by residential neighborhoods, and on the east by a golf course. There is a wooded buffer separating residential areas and the golf course from the facility (Heritage 2000a). The facility itself is covered by a mix of buildings, asphalt, gravel, and vegetation, with very little exposed soil (Heritage 2000a).

The Collis facility sits in the alluvial flood plain of the Mississippi River, and the nearest surface water body is Manufacturers Ditch, which is perennial but with very low flow (Heritage 1994). The ditch receives stormwater runoff from the facility and from mixed-use areas upstream and downstream; it also receives treated wastewater from the facility's NPDES-permitted outfall (Heritage 1998a). Stormwater runoff at the facility also drains into ditches along S. 19th Street and into storm sewers (Heritage 1994).

The surficial geology and hydrogeology of the site is dominated by alluvial materials and weathered bedrock. Unconsolidated materials at the facility consist of layers of clayey silts and silty clays overlying layers of sand and gravel (Heritage 1994). The depth to bedrock ranges from 6 to 118 feet, and the facility is underlain by two bedrock valleys that meet under the facility (Heritage 1994). The uppermost bedrock is Silurian limestone that has been weathered at its surface (Heritage 1994). The Silurian bedrock is underlain by a thick sequence of Ordovician confining beds, then by Cambrian and Ordovician sandstone and limestone aquifers (Heritage 1998a). Monitoring wells at the facility are completed in the unconsolidated material and weathered Silurian bedrock, and the water table in these wells is about 2.5 to 14.3 feet below ground surface (bgs) (Heritage 1994). Groundwater in the unconsolidated material and weathered bedrock flows from south to north and west, toward the ditch (Heritage 2000a). Because of relatively low yields from the surficial materials, the facility production well is completed in Cambrian sandstone, about 1,633 feet bgs (Heritage 1994). Similarly, a drinking water well operated by the municipal water supply (about 0.5 mile from the facility) is 2,020 feet deep (Heritage 1994).

Groundwater

Groundwater samples at the Collis facility have been collected from 1995 to 2000 as part of the RFI (Heritage 2000a, 2000d). At the time of the RFI, the facility had installed 12 monitoring wells and abandoned 8 of them (Heritage 1998a). To complete the RFI, the facility installed an additional 10 wells, 4 of which were completed in bedrock (Heritage 1998a, 2000b). The facility also maintained two piezometers in which it measured water levels and from which it sometimes collected groundwater samples (Heritage 1998a). The locations of monitoring wells are shown on Figure 2. Groundwater samples collected for the RFI and as part of the corrective measures study (in 2000) were analyzed for VOCs, SVOCs, cyanide, and total and dissolved metals (Heritage 1998a). In general, unfiltered samples will have higher concentrations of metals because of the contribution of metal from suspended sediment.

The most contaminated groundwater samples were collected from the wells on the northern, downgradient edge of the facility. Table 1 shows the maximum concentrations of metals, cyanide, and VOCs. None of the groundwater samples collected had detectable concentrations of SVOCs (Heritage 1998a). None of the dissolved metal concentrations exceeded their relevant EPA maximum contaminant level (MCL) or preliminary remediation goal (PRG). Unfiltered samples from well MW-22 had very high concentrations of metals, but this well had excessive suspended solids and was subsequently abandoned (Heritage 2000a). Similarly, the only sample that exceeded the MCL for cyanide was collected from MW-22 (Heritage 1998a). Chlorinated VOCs are the primary constituents of concern in groundwater from the facility. The compounds 1,1-dichloroethene (DCE), 1,2-DCE, trichloroethene (TCE), and vinyl chloride (VC) are all present in concentrations that exceed their relevant MCLs (maximum concentrations of 8 micrograms per liter [µg/l], 1,200 µg/l, 600 µg/l, and 500 µg/l, respectively) (Heritage 1998a, 2000b, 2000c, 2000d).

Table 1 - Maximum Concentrations of Constituents in Groundwater

Constituent	Concentration (μg/l)	Well	Date	EPA MCL (μg/l)	Other Wells Exceeding MCL
Dissolved Metals					<u>a</u> =
Chromium	40	MW-2	August 1995	100	None
Nickel	340	MW-39	May 1996	730*	None
Zinc	680	MW-39	May 1996	11,000*	None
Total Metals					
Arsenic	99	MW-37	September 2000	NA	NA
Cadmium	11	MW-22	July 1997	NA	NA
Chromium	2,600	MW-22	July 1997	NA	NA
Lead	17	MW-22	September 2000	NA	NA
Nickel	810	MW-22	July 1997	NA	NA
Zinc	5,500	MW-22	July 1997	NA	NA
Dissolved Cyanide					
Cyanide	260	MW-22	August 1995	200	None
Total Cyanide					
Cyanide	260	MW-22	August 1995	NA	NA
Volatile Organic Compounds					•
Acetone	32	MW-2	July 1997	610	None
1,1-Dichloroethene	8	MW-39	May 1996	7	
1,2-Dichloroethene (total)	1,200	MW-2	July 1997	70**	MW-34, MW-35, MW-36, MW- 37, MW-38, MW-39
cis-1,2-Dichloroethene	1,100	MW-39	May 1996	70	MW-2, MW-34, MW-35, MW-36, MW-37, MW-39, MW-42
trans-1,2-Dichloroethene	56	MW-39	May 1996	100	None
Toluene	5	MW-38	May 1996	1,000	None
Trichloroethene	600	MW-42	September 2000	5	MW-2, MW-13, MW-34, MW-35 MW-36, PZ-41
Vinyl chloride	500	MW-38	July 1997	2	MW-2, MW-34, MW-35, MW-36 MW-37, MW-39, MW-42, PZ-40

Notes:

Concentrations in bold exceed the MCL (EPA 2002a). Table derived from the 1998 facility investigation and 2000 supplemental investigation (Heritage Environmental Services 1998a, 2000b, 2000c, 2000d).

- * EPA does not specify a MCL for this constituent (EPA 2002a). EPA Region 9 preliminary remediation goal used (EPA 2002b).
- ** Because cis-1,2-dichloroethene (DCE) makes up as much as 90 percent of the total 1,2-DCE concentration, the MCL for cis-1,2-DCE has been used here.
- EPA = U.S. Environmental Protection Agency
- MCL = Maximum contaminant level
- NA = Not applicable. MCLs are established for dissolved concentrations.
- μg/l = Micrograms per liter

Surface and Subsurface Soil

Surface and subsurface soils at the Collis facility are contaminated with metals, VOCs, SVOCs, and PCBs. Surface (collected from a depth of less than 2 feet) and subsurface (collected from a depth of more than 2 feet) soil samples were collected at Collis during site investigations associated with RCRA closure activities and in support of the RFI (Heritage 1998a). Samples were analyzed for metals, cyanide, VOCs, SVOCs, and PCBs. RFI soil sampling locations are shown in Figure 3. In general, metals were detected in the soils throughout the site, VOCs were detected primarily in the northwestern corner of the site, and SVOCs were detected primarily in the northeast corner of the site (Heritage 2000a).

Surface soil at the facility is contaminated with metals, VOCs, SVOCs, and PCBs. Table 2 shows the maximum concentrations of a range of constituents found in surface soil. The highest levels of contamination in surface soil are from SWMU 6, the northeast yard, receiving dock, and outdoor storage area. The only metal that exceeds industrial or residential PRGs is chromium. The maximum concentration of chromium was 6,700 milligrams per kilogram (mg/kg), which exceeds the industrial PRG. Five VOCs – ethylbenzene (maximum concentration of 21 mg/kg), tetrachloroethene (PCE) (6 mg/kg), tetrahydrofuran (140 mg/kg), toluene (820 mg/kg), and TCE (200 mg/kg) – exceeded industrial PRGs, and one, 1,2-DCE (52 mg/kg), exceeded residential PRGs. Seven SVOCs, primarily PAHs, exceeded industrial PRGs – benzo(a)anthracene (maximum of 550 mg/kg), benzo(a)pyrene (540 mg/kg), benzo(k)fluoranthene (estimated 310 mg/kg), chrysene (970 mg/kg), bis(2-ethylhexyl)phthalate (estimated 240 mg/kg), indeno(1,2,3-c,d)pyrene (570 mg/kg), and naphthalene (estimated 210 mg/kg). Finally, two PCBs were detected at the facility – one, Aroclor 1254, at concentrations above residential PRGs, and the other, Aroclor 1260, at concentrations above industrial PRGs. The maximum concentrations were 0.57 mg/kg and 8.5 mg/kg respectively.

Subsurface soil at the facility is contaminated with metals, VOCs, SVOCs, and PCBs. Table 3 shows the maximum concentrations of a range of constituents found in subsurface soil. The highest levels of contamination in subsurface soil are from SWMU 4, the former sludge impoundment area. Three metals exceed industrial PRGs – arsenic (maximum concentration of 47 mg/kg), chromium (13,000 mg/kg), and lead (1,000 mg/kg). Seven VOCs – benzene (maximum concentration of 18 mg/kg), 1,2-dichloropropane (6 mg/kg), ethylbenzene (75 mg/kg), tetrahydrofuran (45 mg/kg), toluene (110 mg/kg), TCE (60 mg/kg), VC (120 mg/kg), and xylene (96 mg/kg) – exceeded industrial PRGs, and one, 1,2-DCE (96 mg/kg), exceeded residential PRGs. Nineteen SVOCs, primarily PAHs, exceeded industrial PRGs (see Table 3 for a list of constituents and concentrations). Finally, two PCBs were detected at the facility at concentrations above their industrial PRGs – Aroclor 1254 (maximum concentration of 1.5 mg/kg) and Aroclor 1260 (7.5 mg/kg).

Table 2 - Constituents Detected in Surface Soil

Constituent	Concentration (mg/kg)	SWMU	Depth (ft bgs)	EPA Region 9 Residential PRG (mg/kg)	EPA Region 9 Industrial PRG (mg/kg)
Metals				1	
Cadmium	10.0	2	1 - 8	37	450
Chromium	6,700.0	1	0.5 - 1.5	210	450
Nickel	240.0	1	0.5 - 1.5	16,000	20,000
Zinc	5,800.0	1	0.5 - 1.5	230,000	100,000
Cyanide	•				
Cyanide	590	4	0 - 2	1,200	12,000
Volatile Organic Compounds					
Acetone	480 J	6	0 - 2	1,600	6,000
Carbon disulfide	9	6	0 - 2.5	360	720
1,2-Dichloroethene (total)	52	2	0 - 4	43*	150*
Ethylbenzene	21	6	0 - 2.5	8.9	20
Methyl ethyl ketone	61 J	6	0 - 2	7,300	27,000
Tetrachloroethene	6	1	0.5 - 1.5	1.5	3.4
Tetrahydrofuran	140	6	0 - 2.5	9.4	21
Toluene	820	6	0 - 2.5	520	520
Trichloroethene	200	2	0 - 4	0.053	0.11
Xylene	27	6	0 - 2.5	270	420
Semivolatile Organic Compound	s				
Benzo(a)anthracene	550	6	0 - 2.5	0.62	2.1
Benzo(a)pyrene	540	6	0 - 2.5	0.062	0.21
Benzo(a)fluoranthene	860	6	0 - 2.5	NA	NA
Benzo(g,h,i)perylene	590	6	0 - 2.5	NA	NA
Benzo(k)fluoranthene	310 J	6	1 - 3	6.2	21
Chrysene	970	6	0 - 2.5	62	210
Di-n-butylphthalate	390	6	0 - 2.5	6,100	62,000
bis(2-Ethylhexyl)phthalate	240 J	6	0 - 2.5	35	120
Fluoranthene	1,400	6	1 - 3	2,300	22,000
Fluorene	280 J	6	0 - 2.5	2,700	26,000
Indeno(1,2,3-c,d)pyrene	570	6	0 - 2.5	0.62	2.1
Naphthalene	210 J	6	0 - 2.5	5.6	190
Phenanthrene	1,900	6	0 - 2.5	NA	NA

Table 2 - Constituents Detected in Surface Soil

Constituent	Concentration (mg/kg)	SWMU	Depth (ft bgs)	EPA Region 9 Residential PRG (mg/kg)	EPA Region 9 Industrial PRG (mg/kg)
Pyrene	2,700	6	0 - 2.5	2,300	29,000
Polychlorinated Biphenyls	3				
Aroclor 1254	0.57	6	0 - 2.5	0.22	0.74
Aroclor 1260	8.5	6	0 - 2.5	0.22	0.74

Notes:

Concentrations in bold exceed industrial soil target concentrations. Concentrations in italics exceed residential soil target concentrations. Table derived from the 1998 RFI (Heritage Environmental Services 1998a).

Because cis-1,2-dichloroethene (DCE) makes up as much as 90 percent of the total 1,2-DCE concentration, the PRG for cis-1,2dichloroethene is used here.

EPA = U.S. Environmental Protection Agency

Estimated concentration ft bgs = Feet below ground surface

Milligrams per kilogram

Not available. EPA Region 9 has not established PRGs for these constituents. NA =

Preliminary remediation goals (EPA 2002b). PRG =

RFI = Resource Conservation and Recovery Act Facility Investigation

SWMU = Solid waste management unit

Table 3 - Constituents Detected in Subsurface Soil

Constituent	Concentration (mg/kg)	SWMU	Depth (ft bgs)	EPA Region 9 Residential PRG (mg/kg)	EPA Region 9 Industrial PRG (mg/kg)
Metals					
Arsenic	47.0	4	2 - 4	0.39	1.6
Cadmium	21.0	4	2 - 4	37	450
Chromium	13,000.0	4	4 - 5	210	450
Lead	1,000.0	4	2 - 4	400	750
Nickel	1,800.0	4	2 - 3	16,000	20,000
Zinc	16,000.0	4	4 - 5	230,000	100,000
Cyanide					
Cyanide	1,200	3	3 - 5	1,200	12,000
Volatile Organic Compounds				•	•
Acetone	440	1	7 - 10	1,600	6,000
Benzene	18	4	6 - 8	0.6	1.3
Carbon disulfide	11	4	2 - 4	360	720
Chlorobenzene	6	4	7 - 9	150	530
1,2-Dichloroethene (total)	96	2	8 - 12	43*	150°
1,2-Dichloropropane	6	1	7 - 10	0.34	0.74
Ethylbenzene	75	4	4 - 7	8.9	20
2-Hexanone	44	4	2 - 4	NA	NA
Methyl ethyl ketone	130	4	2 - 4	7,300	27,000
Styrene	100	4	6 - 8	1,700	1,700
Tetrahydrofuran	45	1	2 - 4	9.4	21
Toluene	67	4	6 - 8	520	520
Trichloroethene	110	1	7 - 10	1.5	3.4
Vinyl chloride	60	3	7 - 9	0.079	0.75
Xylene	120	4	6 - 8	270	420
Semivolatile Organic Compoun	ds				
Acenaphthene	30,000	4	4 -5	3,700	29,000
Anthracene	7,000	4	4 -5	22,000	100,000
Benzo(a)anthracene	91,000	4	4 -5	0.62	2.1
Benzo(a)pyrene	60,000	4	4 -5	0.062	0.21
Benzo(a)fluoranthene	81,000	4	4 -5	NA	NA
Benzo(g,h,i)perylene	36,000	4	4 -5	NA	NA
Benzo(k)fluoranthene	25,000	4	4 -5	6.2	21

Page 11

Table 3 - Constituents Detected in Subsurface Soil

Constituent	Concentration (mg/kg)	SWMU	Depth (ft bgs)	EPA Region 9 Residential PRG (mg/kg)	EPA Region 9 Industrial PRG (mg/kg)	
Carbazole	20,000	4	4 -5	24	86	
Chrysene	77,000	4	4 -5	62	210	
Dibenz(a,h)anthracene	8,400	4	4 -5	0.062	0.21	
Dibenzofuran	32,000	4	4 -5	290	3,100	
1,3-Dichlorobenzene	410	4	7 - 9	16	63	
1,4-Dichlorobenzene	1,200	4	7 - 9	3.4	7.9	
bis(2-Ethylhexyl)phthalate	1,600	4	4 -5	35	120	
Fluoranthene	270,000	4	4 -5	2,300	22,000	
Fluorene	46,000	4	4 -5	2,700	26,000	
Indeno(1,2,3-c,d)pyrene	32,000	4	4 -5	0.62	2.1	
2-Methylnaphthene	13,000	4	4 -5	NA	NA	
4-Methylphenol	980 J	4	2 - 4	310	3,100	
Naphthalene	19,000	4	4 -5	5.6	190	
Phenanthrene	350,000	4	4 -5	NA	NA	
Pyrene	260,000	4	4 -5	2,300	29,000	
1,2,4-Trichlorobenzene	1,400	4	7 - 9	650	3,000	
Polychlorinated Biphenyls	•			***************************************		
Aroclor 1254	1.50	4	2 - 4	0.22	0.74	
Aroclor 1260	7.5	4	4 - 7	0.22	0.74	

Notes:

Concentrations in bold exceed industrial soil target concentrations. Concentrations in italics exceed residential soil target concentrations. Table derived from the 1998 RFI (Heritage Environmental Services 1998a).

*= Because cis-1,2-dichloroethene (DCE) makes up as much as 90 percent of the total 1,2-DCE concentration, the PRG for cis-1,2-dichloroethene is used here.

EPA = U.S. Environmental Protection Agency

J = Estimated concentration ft bgs = Feet below ground surface

mg/kg = Milligrams per kilogram

NA = Not available. EPA Region 9 has not established PRGs for these constituents.

PRG = Preliminary remediation goals (EPA 2002b).

RFI = Resource Conservation and Recovery Act Facility Investigation

SWMU = Solid waste management unit

Surface Water

Surface water from Manufacturers Ditch near the facility is not contaminated. Surface water samples were collected during the RFI and as part of an additional investigation in 2000 (Heritage 1998a, 2000b). Figures 1, 2, and 3 show the sampling locations. Surface water was analyzed for VOCs, cyanide, and metals (both total and dissolved). Acetone and cyanide were detected in the RFI surface water samples (maximum concentrations of 76 g/l and

40 μg/l) but at concentrations below the Iowa Criteria for Chemical Constituents for Type C waters (Iowa Administrative Code, Division 567, Chapter 61) (Heritage 1998a). Surface water samples collected in 2000 had detectable concentrations of dissolved barium (maximum of 99 μg/l) and dissolved cyanide (8 μg/l), but no detectable VOCs (Heritage 2000b). Again, concentrations were below the Iowa Criteria for Chemical Constituents.

Sediments

Sediment at the Collis facility is contaminated with metals and VOCs, but concentrations may be declining. Sediment samples were collected during the RFI and in an additional investigation in 2000 (Heritage 1998a, 2000b). Samples were analyzed for metals, cyanide, and VOCs. Figures 1, 2, and 3 show the sampling locations. In general, concentrations were much lower in samples from the 2000 sampling event than in those from the 1998 sampling event (Heritage 2000b). Moreover, no chlorinated VOCs were detected in samples from the 2000 event (Heritage 2000b).

Table 4 shows the maximum concentrations of a range of constituents found in sediment. The highest levels of contamination in sediment were in samples SD-04 and SD-05, which were collected from the ditch south of S. 19th Street. Sample SD-09 also had high concentrations of VOCs. However, SD-09 was collected at a distance of about 0.5 mile from the facility, and samples collected from locations between the facility and SD-09's location had lower concentrations of VOCs than SD-09. As a result, the contamination in SD-09 may be attributable to other facilities. The only metal that exceeds industrial or residential PRGs is chromium. The maximum concentration of chromium was 1,700 milligrams per kilogram (mg/kg), which exceeds the industrial PRG. Two VOCs were detected at concentrations above PRGs – one, 1,2-DCE, at concentrations above residential PRGs, and the other, VC, at concentrations above industrial PRGs. The maximum concentrations were 120 mg/kg and 310 mg/kg, respectively. Both VOC concentrations were estimated.

Table 4 - Constituents Detected in Sediment

Constituent	Concentration (mg/kg)	Sample	EPA Region 9 Residential PRG (mg/kg)	EPA Region 9 Industrial PRG (mg/kg)
Metals				
Chromium	1,700.0	SD-04	210	450
Nickel	31.0	SD-04	16,000	20,000
Zinc	2,900.0	SD-04	230,000	100,000
Cyanide			1	
Cyanide	49	SD-04	1,200	12,000
Volatile Organic Compounds	,			
Acetone	180	SD-04	1,600	6,000
1,2-Dichloroethene (total)	120 J	SD-05	43*	150*
Methyl ethyl ketone	38	SD-03	7,300	27,000
Toluene	5	SD-04	520	520
Vinyl Chloride	310 J	SD-05	0.079	0.75
Xylene	9.0	SD-04	270	420

Notes:

Concentrations in bold exceed industrial soil target concentrations. Concentrations in italics exceed residential soil target concentrations. Table derived from the 1998 RFI (Heritage Environmental Services 1998a). PRGs have not been established for sediment.

Because cis-1,2-dichloroethene (DCE) makes up as much as 90 percent of the total 1,2-DCE concentration, thePRG for cis-1,2-dichloroethene is used here.

EPA = U.S. Environmental Protection Agency

J = Estimated concentration

NA = Not available. EPA Region 9 has not established PRGs for these constituents.

mg/kg = Milligrams per kilogram

PRG = Preliminary remediation goals (EPA 2002b).

RFI = Resource Conservation and Recovery Act Facility Investigation

Indoor Air

Because of the presence of VOCs in shallow groundwater and surface soil at the facility, indoor air likely is contaminated with organic vapors. Vapors from contaminated soil and groundwater may intrude into buildings at the facility through cracks in the foundation or through underground electrical conduits or plumbing. No indoor air sampling has been conducted at Collis. However, EPA guidance can be used to determine if indoor air contamination is likely at the facility, and the Johnson-Ettinger model can be used to estimate indoor air concentrations at locations that meet the screening criteria (2002c). The results of the screening and models are provided in Appendices A and B.

The first level of the EPA's indoor air screening consists of two criteria, both of which are met at the Collis facility. First, environmental media at the site must be contaminated by constituents that are sufficiently volatile and

sufficiently toxic. Groundwater and soil at the facility are contaminated with several constituents that meet this standard, in particular, 1,1-DCE, 1,2-DCE, TCE, and VC in groundwater. Because most of the 1,2-DCE at the facility is *cis*-1,2-DCE (see Table 1), reported concentrations of total 1,2-DCE are considered *cis*-1,2-DCE for the purposes of screening and modeling. Second, the contaminated media must be present under inhabited buildings. Three wells – MW-2, MW-39, and PZ-40 – are located within 50 feet of the main building and have concentrations of VOCs that exceed EPA MCLs (see Figure 2 and Table 1). Because of the proximity of these wells to the main building and the excessive concentrations of VOCs in all three of these wells, it is reasonable to assume that groundwater under the main building is contaminated.

The next level of the EPA's indoor air screening compares the concentrations of contaminants to screening levels. Concentrations of VOCs in groundwater at Collis are high enough to raise concerns about potential indoor air contamination. The screening levels are based on concentrations needed to generate vapors in indoor air at levels that would exceed risk levels for ambient air. Tables 2 and 3 in Appendix A shows the maximum concentrations of select VOCs in groundwater, compared to the initial screening concentrations. The vapor attenuation factor of $5x10^{-4}$ was estimated based on depth to groundwater (only 2.5 feet bgs in the three wells nearest the facility) and the type of soil at the site (considered loamy sand for modeling purposes) (Heritage 1998a, 2000b). Based on this level of screening, 1,2-DCE, TCE, and VC may cause contamination of indoor air and should be included in any modeling.

The last level of the EPA's indoor air screening specifies the use of a model to estimate the risk generated by organic vapors in indoor air. Based on the results of Johnson-Ettinger models, volatilization of organic constituents in groundwater does cause an increase in risk and contaminated indoor air (see Appendix B). Table 5 shows the results of the Johnson-Ettinger models. Of the three compounds modeled, VC has an incremental risk above the minimum threshold of 10⁻⁶. The hazard quotients, which estimate the noncarcinogenic risks, total less than 1, indicating that this component of risk is not significant.

Table 5 - Estimated Incremental Risk and Hazard Quotients, Indoor Air

Constituent	Concentration in Groundwater (µg/l)	Well	Date	Incremental Risk (carcinogen)	Hazard Quotient (noncarcinogen)
1,1-Dichloroethene	8	MW-39	May 1996	Not modeled	Not modeled
1,2-Dichloroethene (total)*	1,200	MW-2	July 1997	Not applicable	9.89x10 ⁻²
cis-1,2-Dichloroethene	840	MW-2	September 2000	Not modeled	Not modeled
trans-1,2-Dichloroethene	56	MW-39	May 1996	Not modeled	Not modeled
Trichloroethene	92	MW-2	October 1997	4.65x10 ⁻⁷	Not applicable
Vinyl chloride	200	MW-39	July 2000	1.07x10 ⁻⁵	5.67x10 ⁻²

Notes:

Concentrations in Table 5 are derived from the 1998 RFI and 2000 supplemental investigation (Heritage Environmental Services 1998a, 2000b, 2000c, 2000d).

μg/l = micrograms per liter

Because *cis*-1,2-dichloroethene (DCE) makes up as much as 90 percent of the total 1,2-DCE concentration, the total 1,2-DCE concentration was used as *cis*-1,2-DCE for modeling.

Outdoor Air

Because confining features are absent, concentrations of organic vapors in outdoor air are probably not significant. Because most of the facility is covered with buildings, asphalt, gravel, and vegetation (Heritage 2000a), contamination of indoor or outdoor air with soil particulate likely is minimal.

3. Are there **complete pathways** between "contamination" and human receptors such that exposures can be reasonably expected under the current (land- and groundwater-use) conditions?

Summary Exposure Pathway Evaluation Table Potential Human Receptors (Under Current Conditions)										
"Contaminated" Media	Residents	Workers	Day-Care	Construction	Trespassers	Recreation	Food ³			
Groundwater	NO	NO	NO	YES	NO	NO	NO			
Air (indoors)	NO	YES	NO	NO	NO	NO	NO			
Soil (surface, e.g., <2 ft)	NO	NO	NO	YES	NO	NO	NO			
Surface Water	1 14		- 25	_		_	_			
Sediment	NO	NO	NO	YES	YES	NO	NO			
Soil (subsurface e.g., >2 ft)	NO	NO	NO	YES	NO	NO	NO			
Air (outdoors)	-	-	-	_	-	-	-			

Instructions for Summary Exposure Pathway Evaluation Table

- 1. Strike-out specific Media including Human Receptors' spaces for Media which are not "contaminated") as identified in #2 above.
- 2. enter "yes" or "no" for potential "completeness" under each "Contaminated" Media -- Human Receptor combination (Pathway).

Note: In order to focus the evaluation to the most probable combinations some potential "Contaminated" Media - Human Receptor combinations (Pathways) do not have check spaces ("___"). While these combinations may not be probable in most situations they may be possible in some settings and should be added as necessary.

	If no (pathways are not complete for any contaminated media-receptor combination) - skip to #6, and enter "YE" status code, after explaining and/or referencing condition(s) in-place, whether natural or man-made, preventing a complete exposure pathway from each contaminated medium (e.g., use optional <u>Pathway Evaluation Work Shee</u> tto analyze major pathways).
X	If yes (pathways are complete for any "Contaminated" Media - Human Receptor combination) - continue after providing supporting explanation.
	If unknown (for any "Contaminated" Media - Human Receptor combination) - skip to #6 and enter "IN" status code

³Indirect Pathway/Receptor (e.g., vegetables, fruits, crops, meat and dairy products, fish, shellfish, etc.)

Rationale and Reference(s)

Two media – surface water and outdoor air – can be excluded from further consideration, because no evidence indicates that these media are contaminated at the Collis facility.

All classes of receptors must be evaluated for potential exposure. Maps of the facility indicate the facility is surrounded by a fence (see Figure 2). However, it is unclear how high or how well maintained the fence is. As a result, trespassers on the property are possible. Collis is still operational and employs 285 employees, in 24 hour per day, 5 day per week operations (EPA 2001), so facility workers must be considered. No information is available about Collis's use of contract construction workers. However, it is likely that any onsite excavation, construction, or utility work would be performed by contract workers, and this class of receptors must be considered. The properties immediately south of Collis property are residential (see Figure 1), and a day care center and school are located within 1 mile of the facility (Switchboard.com 2003). The closest day care is the Stay N Play center, which is about 0.5 mile south of the Collis property. The property immediately east of the Collis facility is the Clinton Country Club. Because the country club operates an irrigation well (see Appendix C), recreational users may be exposed to contaminated groundwater; as a result, recreational uses should be considered. Finally, because Manufacturers Ditch is a perennial surface water body, it may be used by recreational fishermen. Therefore, food receptors must be included.

Contract workers may be exposed to contaminated soil. Because most surface soil at Collis is covered with pavement, crushed rock, buildings, or vegetation (Heritage 2000a), trespassers and Collis workers likely are not exposed to contaminated surface soil. Residential, day care, and recreational receptors are not likely to come into contact with contaminated surface soil at the Collis facility, which is surrounded by a fence. The facility's location in a developed area makes the use of the facility to grow food unlikely. However, any excavation workers might be exposed to contaminated soils and sediments.

Only contract excavation workers likely are exposed to contaminated subsurface soils. Facility workers, trespassers, nearby residents, and day care children likely do not come into contact with soils deeper than 2 feet bgs. The facility's location in a developed area makes the use of the facility to grow food unlikely.

No receptors likely are exposed to contaminated groundwater by ingestion. Appendix C provides a list of wells within 1 mile of the facility (Iowa Department of Natural Resources [IDNR] 2003). The surrounding community is part of a utility district that provides drinking water. The city utility does collect some of its drinking water from a well about 0.5 miles from the facility. However, this well is more than 2,000 feet deep, completed in the Cambrian sandstone and separated from the contaminated surface aquifers by thick confining beds (Heritage 1998a). Similarly, the wells at Western Ice and Swift & Co. are more than 1,000 feet deep. The potential for contamination to migrate into any of these wells is very low (Heritage 1998a). A second municipal well that is only 165 feet deep is located at the city's sewage treatment plant (IDNR 2003). Because of its location, it is unlikely that this well is used to provide drinking water. As a result, facility workers, contract workers, trespassers, recreational users, nearby residents, day care children, and food consumers all are unlikely to be exposed to contaminated groundwater through ingestion.

Groundwater exposure pathways also may be completed by dermal contact. Unattended monitoring wells provide a pathway through which trespassers could be exposed to contaminated groundwater. However, the standard practice of padlocking well covers make completion of this pathway unlikely. Wells used by the Collis facility and surrounding industrial and recreational operations also are deep. The Collis process well is more than 1,600 feet deep, and the well used to irrigate the golf course is more than 850 feet deep. As a result, it is unlikely that facility workers or recreational users would be exposed to contaminated groundwater through dermal contact. Of the wells located within 1 mile of the facility, three are less than 200 feet deep. These wells are all designated as private use, and they are located in residential neighborhoods. However, none of these wells are located downgradient from the Collis facility and are, therefore, not likely to be contaminated by releases from the Collis facility. As a result,

residential and day-care exposure to contaminated groundwater can be excluded. However, because the water table at the site is as shallow as 2.5 feet bgs, contract excavation workers may come into dermal contact with contaminated groundwater.

Only facility employees likely are exposed to contaminated indoor air. Although contract construction and utility workers may spend time indoors at the Collis facility, their exposure to organic vapors typically would be limited in duration. Trespassers, recreational users, nearby residents, and day care students would not be expected to spend any time indoors at Collis and therefore would not be exposed. Currently, the facility is not operating a soil-vapor extraction system or any other remediation system to control the infiltration of organic vapors from groundwater. As a result, facility workers likely are being exposed to VOCs in indoor air.

Trespassers and construction workers may be exposed to contaminated sediment. However, Manufacturers Ditch is not part of an operational area of the facility. As a result, it is unlikely that facility workers would be exposed to contaminated sediment in the course of their normal operations. In addition, because of the low flow of the stream and the industrial setting of the ditch in the area of the facility, it is unlikely that recreational, residential, or day-care receptors would be making use of the ditch (Heritage 1998a), and these exposure pathways can be excluded. Given the low flow in the ditch and its industrial setting, any food use probably is uncommon or sporadic. As a result, the food pathway can be excluded. However, trespassers may come into contact with contaminated sediment. Contract construction, excavation, or utility workers may be exposed to sediment when maintaining or repairing the facilities permitted outfall.

4.	"significant" (i greater in magnitude "levels" (used to though low) and	es from any of the complete pathways identified in #3 be reasonably expected to be i.e., potentially "unacceptable" because exposures can be reasonably expected to be: 1) tude (intensity, frequency and/or duration) than assumed in the derivation of the acceptable identify the "contamination"); or 2) the combination of exposure magnitude (perhaps even contaminant concentrations (which may be substantially above the acceptable "levels") reater than acceptable risks)?
	<u>_x</u>	If no (exposures can not be reasonably expected to be significant (i.e., potentially "unacceptable") for any complete exposure pathway) - skip to #6 and enter "YE" status code after explaining and/or referencing documentation justifying why the exposures (from each of the complete pathways) to "contamination" (identified in #3) are not expected to be "significant."
		If yes (exposures could be reasonably expected to be "significant" (i.e., potentially "unacceptable") for any complete exposure pathway) - continue after providing a description (of each potentially "unacceptable" exposure pathway) and explaining and/or referencing documentation justifying why the exposures (from each of the remaining complete pathways) to "contamination" (identified in #3) are not expected to be "significant."
		If unknown (for any complete pathway) - skip to #6 and enter "IN" status code

Rationale and Reference(s):

Exposures can be considered significant if the duration or intensity of exposure to contaminated materials exceeds calculated screening levels or if the level of contamination substantially exceeds screening levels. Completed exposure pathways at Collis include:

- 1. contract construction workers groundwater, surface soil, subsurface soil, and sediment
- 2. facility workers indoor air
- trespassers sediment

While repairing or installing utilities or other excavation work, contract construction workers and utility workers would be exposed to contaminated groundwater, surface soil, subsurface soil, and sediment with concentrations of contaminants that exceed EPA Region 9 PRGs. However, because they are not full-time employees on site, their exposure is limited in duration. EPA Region 9 industrial PRGs for soil are calculated based on assumptions of 25 years, 250 days per year, of exposure (EPA 2002b). Because of the limited period of contact, exposure of contract construction workers to hazardous constituents in soil or sediment likely is not significant. Groundwater target concentrations are based predominantly on ingestion of water and are not applicable to dermal contact alone. The level of exposure of contract construction and utility workers to hazardous constituents in groundwater likely is not significant.

Because the channel of Manufacturers Ditch is open to the air, trespassers may come into contact with contaminated sediments. However, it is unlikely that trespassers will spend significant amounts of time in the ditch, given the low

⁴If there is any question on whether the identified exposures are "significant" (i.e., potentially "unacceptable") consult a human health Risk Assessment specialist with appropriate education, training and experience.

flow of the stream and the industrial setting of the ditch in the area of the facility. As a result, the exposure of trespassers to hazardous constituents in sediment likely is not significant.

Collis facility workers could be exposed to contaminated indoor air as a result of contaminated groundwater that flows beneath the facility. VOC vapors from contaminated groundwater could enter the facility through cracks in the floors and foundation. Results of the vapor intrusion screening indicate that potential contamination could result from VOC contamination of soils and groundwater present at Collis (see Appendix A). Based on the model, only VC exceeded a 10⁻⁶ incremental risk, with a value of 1.1x10⁻⁵. However, because the incremental risk from VC is less than 10⁻⁴, it is not significant.

	If yes (all "significant" exposures have been shown to be within acceptable limits) - continue and enter "YE" after summarizing and referencing documentation justifying why all "significant" exposures to "contamination" are within acceptable limits (e.g., a site-specific Human Health Risk Assessment).
	If no (there are current exposures that can be reasonably expected to be "unacceptable")-continue and enter "NO" status code after providing a description of each potentially "unacceptable" exposure.
	If unknown (for any potentially "unacceptable" exposure) - continue and enter "IN" status code

Page 22

code	k the appropriate RCRA Info status codes for the Current Human Exposures Under Control EI event (CA725), and obtain Supervisor (or appropriate Manager) signature and date on the EI determination w (and attach appropriate supporting documentation as well as a map of the facility):
	YE - Yes, "Current Human Exposures Under Control" has been verified. Based on a review of the information contained in this EI Determination, "Current Human Exposures" are expected to be "Under Control" at the Collis Inc. facility, EPA ID #IAD047303771, located at 2005 S. 19 th Street, Clinton, Iowa, under current and reasonably expected conditions. This determination will be re-evaluated when the Agency/State becomes aware of significant changes at the facility.
	NO - "Current Human Exposures" are NOT "Under Control."
	IN - More information is needed to make a determination.
Completed by	(signature) Wray Rohman Date 9-26-03
	Project Manager, RCRA Corrective Action & Permits Branch
Supervisor	EPA Region 7 (signature) John Smith
	Branch Chief, RCRA Corrective Action & Permits Branch
	EPA Region 7
Locations who	ere References may be found:
RCR 901 1	Region 7 Headquarters A Files North 5 th Street as City, Kansas 66101
	none and e-mail numbers
Contact telepi	ione and c-main numbers

FINAL NOTE: THE HUMAN EXPOSURES EI IS A QUALITATIVE SCREENING OF EXPOSURES AND THE DETERMINATIONS WITHIN THIS DOCUMENT SHOULD NOT BE USED AS THE SOLE BASIS FOR RESTRICTING THE SCOPE OF MORE DETAILED (E.G., SITE-SPECIFIC) ASSESSMENTS OF RISK.

Wray Rohrman (913) 551-7543


rohrman.wray@epa.gov


REFERENCES


- Environmental Protection Agency, U.S. (EPA). 2001. "Report of RCRA Compliance Inspection at Collis, Inc."
 March 14.
- EPA. 2002a. "List of Contaminants and their MCLs (Maximum Contaminant Levels)." EPA 816-F-02-013. July.
- EPA. 2002b. "Region 9 Preliminary Remediation Goals." October 10.
- EPA. 2002c. "Draft Guidance for Evaluating the Vapor Intrusion to Indoor Air Pathway from Groundwater and Soils." November 29.
- Heritage Environmental Services, LLC (Heritage). 1994. "RCRA (Resource Conservation and Recovery Act) Facility Investigation Current Conditions Report, Collis, Inc." January 27.
- Heritage. 1998a. "Final Remedial Facility Investigation Report, Collis, Inc." March 27.
- Heritage. 1998b. "Response to RFI (RCRA Facility Investigation) Review Comments." October 1.
- Heritage. 2000a. "RCRA Facility Investigation Corrective Measures Work Plan, Collis, Inc." January 12.
- Heritage. 2000b. "Summary of Additional Investigative Activities Interim Report." September 29.
- Heritage. 2000c. "Progress Report 47: RCRA Facility Investigation, Collis, Inc." November 7.
- Heritage. 2000d. "Progress Report 48: RCRA Facility Investigation, Collis, Inc." December 8.
- Iowa Department of Natural Resources. 2003. "GEOSAM." Accessed on August 19. On-line Address: http://gsbdata.igsb.uiowa.edu/geosam/
- Switchboard.com. 2003. Accessed on August 22. On-line Address: www.switchboard.com

FIGURES

(3 pages)







APPENDIX A COLLIS INC. INDOOR AIR SCREENING

VAPOR INTRUSION PATHWAY SUMMARY PAGE

Facility Name: Collis Inc. (IAD047303771)
Facility Address: 2005 S. 19th Street, Clinton, IA 52732
Primary Screening Summary
Q1: Constituents of concern Identified? X Yes
No (If NO, skip to the conclusion section below and check NO to indicate the pathway is <i>incomplete</i> .)
Q2: Currently inhabited buildings near subsurface contamination?
Areas of future concern near subsurface contamination?
Q3: Immediate Actions Warranted? YesX_No
Secondary Screening Summary
Vapor source identified: X Groundwater
Soil Insufficient Data
Indoor air data available?
Yes No
Indoor air concentrations exceed target levels?
Yes No
X Not applicable

Subsurface data evaluation: (Underline appropriate answers below)

Medium	Q4 Levels Exceeded?	Q5 Levels Exceeded?	Data Indicates Pathway is Complete?
Groundwater	<u>YES</u> / NO / NA / INS	<u>YES</u> / NO / NA / INS	<u>YES</u> / NO / INS
Soil Gas	YES / NO / NA / <u>INS</u>	YES / NO / NA / INS	YES / NO / <u>INS</u>

Groundwater	<u>YES</u> / NO / NA / INS	<u>YES</u> / NO / NA / INS	<u>YES</u> / NO / INS
Soil Gas	YES / NO / NA / <u>INS</u>	YES / NO / NA / <u>INS</u>	YES / NO / <u>INS</u>
Notes:			
NA Not applicable INS Insufficient data a	vailable to make a determi	nation	
Site-Specific Summary			
		tion, potential preferential p ed to identify the most-likel	
conceptual site model. If of impacted areas to sample. Human Exposures Under Of determination. Current Hureasonable conclusion by Ithe vapor intrusion pathwa	ther means were used, doc EPA recommends that pre Control EI determinations man Exposures Under Cor EPA or the State that curre y and current land use con to that the Pathway is Inco	appropriate and applicable in cument how you determined dictive modeling can be use without confirmatory samplated EI determinations are in int human exposures are und ditions. Therefore, if condu- complete and/or does not pos	the potentially most ed to support Current ling to support this intended to reflect a der control with regard to acting evaluation for an
NG 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	to be adequately protective	ing and does the model pred e to support Current Human	
Do subslab vapor concenti Yes No N/A	rations exceed target levels	s?	
Do indoor air concentratio Yes No	ons exceed target levels?		

Conclusion

Is there a Complete Pathway for subsurface vapor intrusion to indoor air?

		he appropriate conclusion for the Subsurface Vapor to Indoor Air Pathway evaluation and ng documentation as well as a map of the facility.
***************************************	_NO -	The "Subsurface Vapor Intrusion to Indoor Air Pathway" has been verified to be incomplete for thefacility, EPA ID #_, located at
This de		tion is based on a review of site information, as suggested in this guidance, check as
) ————————————————————————————————————	For current and reasonably expected conditions, or Based on performance monitoring evaluations for engineered exposure controls. This determination may be re-evaluated, where appropriate, when the Agency/State becomes aware of any significant changes at the facility.
X		Γhe "Subsurface Vapor Intrusion to Indoor Air Pathway" is Complete. Engineered s, avoidance actions, or removal actions taken include:
	None	

	UNKN	OWN - More information is needed to make a determination.

Table 1: Question 1 Summary Sheet.

CAS No.	Chemical	Is Chemical Sufficiently Toxic? ¹	Is Chemical Sufficiently Volatile? 2	Check Here it Known or Reasonably Suspected To Be Present ³
	Acenaphthene	YES	YES	Derresent
	Acetaldehyde	YES	YES	
	Acetone	YES	YES	
	Acetonitrile	YES	YES	
98862	Acetophenone	YES	YES	
107028	Acrolein	YES	YES	
	Acrylonitrile	YES	YES	
309002		YES	YES	
	alpha-HCH (alpha-BHC)	YES	YES	
	Aniline	YES	NO	NA
	Anthracene	NO	YES	NA
	Benz(a)anthracene	YES	NO VES	NA
	Benzaldehyde	YES YES	YES YES	-
	Benzene Benzo(a)pyrene	YES	NO YES	NA
	Benzo(a)pyrene Benzo(b)fluoranthene	YES	YES	INA
	Benzo(k)fluoranthene	NO	NO	NA
	Benzoic Acid	NO	NO	NA NA
	Benzyl alcohol	YES	NO	NA
	Benzylchloride	YES	YES	
	beta-Chloronaphthalene	YES	YES	
319857	beta-HCH (beta-BHC)	YES	NO	NA
	Biphenyl	YES	YES	
111444	Bis(2-chloroethyl)ether	YES	YES	
	Bis(2-chloroisopropyl)ether	YES	YES	
	Bis(2-ethylhexyl)phthalate	NO	NO	NA
	Bis(chloromethyl)ether	YES	YES	
	Bromodichloromethane	YES	YES	
	Bromoform	YES	YES	
	1,3-Butadiene	YES	YES NO	NA NA
/1363	Butanol Butyl benzyl phthalate	YES NO	NO NO	NA NA
	Carbazole	YES	NO	NA NA
	Carbon disulfide	YES	YES	100
	Carbon tetrachloride	YES	YES	<u> </u>
	Chlordane	YES	YES	1
	2-Chloro-1,3-butadiene (chloroprene)	YES	YES	
	Chlorobenzene	YES	YES	
	1-Chlorobutane	YES	YES	
124481	Chlorodibromomethane	YES	YES	5
	Chlorodifluoromethane	YES	YES	
	Chloroethane (ethyl chloride)	YES	YES	
	Chloroform	YES	YES	
	2-Chlorophenol	YES	YES	-
	2-Chloropropane	YES	YES	-
	Chrysene	YES	YES	
	cis-1,2-Dichloroethylene Crotonaldehyde (2-butenal)	YES YES	YES YES	-
	Cumene (z-butenar)	YES	YES	-
72548		YES	NO	NA
72559		YES	YES	1
50293		YES	NO	NA
	Dibenz(a,h)anthracene	YES	NO	NA
	Dibenzofuran	YES	YES	
	1,2-Dibromo-3-chloropropane	YES	YES	
	1,2-Dibromoethane (ethylene dibromide)	YES	YES	
	1,3-Dichlorobenzene	YES	YES	
05501	1,2-Dichlorobenzene	YES	YES	
90001				
106467	1,4-Dichlorobenzene 3,3-Dichlorobenzidine	YES YES	YES NO	NA

Table 1: Question 1 Summary Sheet.

CAS No.	Chemical	Is Chemical Sufficiently Toxic? 1	Is Chemical Sufficiently Volatile? ²	Check Here if Known or Reasonably Suspected To Be Present ³
	1,1-Dichloroethane	YES	YES	
	1,2-Dichloroethane	YES	YES	
	1,1-Dichloroethylene	YES	YES	
	2,4-Dichlorophenol	YES	NO	NA
78875	1,2-Dichloropropane	YES	YES	
	1,3-Dichloropropene Dieldrin	YES	YES YES	
	Diethylphthalate	YES	NO NO	NA
	2,4-Dimethylphenol	YES	NO	NA NA
	Dimethylphthalate	NA NA	NO	NA NA
	Di-n-butyl phthalate	NO	NO NO	NA NA
	4,6-Dinitro-2-methylphenol (4,6-dinitro-o-cresol)	YES	NO	NA NA
	2,4-Dinitrophenol	YES	NO	NA
	2,4-Dinitrotoluene	YES	NO	NA
	2,6-Dinitrotoluene	YES	NO	NA
117840	Di-n-octyl phthalate	NO	YES	NA
	Endosulfan	YES	YES	
	Endrin	YES	NO	NA
	Epichlorohydrin	YES	YES	
	Ethyl ether	YES	YES	Access to the second
	Ethylacetate	YES	YES	
	Ethylbenzene	YES	YES	
	Ethylene oxide	YES	YES	
	Ethylmethacrylate Fluoranthene	YES NO	YES YES	NA
	Fluorene	YES	YES	NA NA
110009	. 166143.15	YES	YES	
	gamma-HCH (Lindane)	YES	YES	
	Heptachlor	YES	YES	
	Heptachlor epoxide	YES	NO	NA
	Hexachloro-1,3-butadiene	YES	YES	
118741	Hexachlorobenzene	YES	YES	
77474	Hexachlorocyclopentadiene	YES	YES	
	Hexachloroethane	YES	YES	
	Hexane	YES	YES	
	Hydrogen cyanide	YES	YES	
	Indeno(1,2,3-cd)pyrene	NO	NO	NA
	Isobutanol	YES	YES	110
	Isophorone Mercury (elemental)	YES YES	NO YES	NA
	Methacrylonitrile	YES	YES	
	Methoxychlor	YES	YES	
	Methyl acetate	YES	YES	
	Methyl acrylate	YES	YES	
	Methyl bromide	YES	YES	
	Methyl chloride (chloromethane)	YES	YES	
	Methylcyclohexane	YES	YES	
	Methylene bromide	YES	YES	
	Methylene chloride	YES	YES	
	Methylethylketone (2-butanone)	YES	YES	
108101	Methylisobutylketone	YES	YES	
80626	Methylmethacrylate	YES	YES	
	2-Methylnaphthalene	YES	YES	
	3-Methylphenol (m-cresol)	YES	NO	NA
	2-Methylphenol (o-cresol)	YES	NO	NA
	4-Methylphenol (p-cresol)	YES	NO	NA
	m-Nitrotoluene	YES	NO	NA
1634044		YES	YES	
	m-Xylene Naphthalene	YES YES	YES YES	
			1 150	

Table 1: Question 1 Summary Sheet.

		Is Chemical Sufficiently	Is Chemical Sufficiently Volatile? 2	Check Here if Known or Reasonably Suspected To Be Present ³	
CAS No.	Chemical	Toxic? 1	YES	Be Present	
	Nitrobenzene	YES YES	NO YES	NA	
	4-Nitrophenol	YES	YES	INA	
	2-Nitropropane	YES	YES		
	N-Nitroso-di-n-butylamine	YES	NO TES	NA NA	
	N-Nitrosodi-n-propylamine	YES	NO NO	NA NA	
	N-Nitrosodiphenylamine	YES	YES	INA	
	n-Propylbenzene o-Nitrotoluene	YES	YES		
		YES	YES		
	o-Xylene	YES	NO NO	NA	
	p-Chloroaniline Pentachlorophenol	YES	NO	NA NA	
108952		YES	NO	NA NA	
	p-Nitrotoluene	YES	NO	NA NA	
	p-Xylene	YES	YES	I INC	
	Pyrene	YES	YES	-	
110961	Pyridine	YES	NO	NA	
	sec-Butylbenzene	YES	YES	100	
	Styrene	YES	YES		
98066	tert-Butylbenzene	YES	YES		
	1,1,1,2-Tetrachloroethane	YES	YES		
	1.1.2.2-Tetrachloroethane	YES	YES		
	Tetrachloroethylene	YES	YES		
	Toluene	YES	YES		
	Toxaphene	YES	NO	NA	
	trans-1,2-Dichloroethylene	YES	YES	V	
76131	1.1.2-Trichloro-1,2,2-trifluoroethane	YES	YES		
	1,2,4-Trichlorobenzene	YES	YES		
	1,1,2-Trichloroethane	YES	YES		
	1,1,1-Trichloroethane	YES	YES		
	Trichloroethylene	YES	YES		
	Trichlorofluoromethane	YES	YES		
95954	2,4,5-Trichlorophenol	YES	NO	NA	
	2,4,6-Trichlorophenol	YES	NO	NA	
96184	1,2,3-Trichloropropane	YES	YES		
	1,2,4-Trimethylbenzene	YES	YES		
	1,3,5-Trimethylbenzene	YES	YES		
108054	Vinyl acetate	YES	YES	F000250331100555	
75014	Vinyl chloride (chloroethene)	YES	YES		

¹ A chemical is considered sufficiently toxic if the vapor concentration of the pure component (see Appendix D) poses an incremental lifetime cancer risk greater than 10⁶ or a non-cancer hazard index greater than 1.

² A chemical is considered sufficiently volatile if its Henry's Law Constant is 1 x 10⁻⁵ atm-m³/mol or greater (US EPA, 1991).

³ Users should check off compounds that meet the criteria for toxicity <u>and</u> volatility and are known or reasonably suspected to be present.

Table 2a: Question 4 Generic Screening Levels and Summary Sheet 4 Risk = 1 x 10 4

CAS No.	Chanical	Compounds with Provisional Toxicity Data Extrapolated From Oral Chemical Sources		with Provisional Toxicity Data Extrapolated From Oral		Target Indo Concentration Both the Presci Level and the Ta Index [R=10 ⁴ , H	to Satisfy ribed Risk rget Hazard	Measured or Reasonably Estimated Indoor Air Concentration [if available]	Target Shallow Concentration Co to Target Ind Concentration Wt Gas to Indoor Air Factor=I Concentration	rresponding door Air here the Soil Attenuation 0.1	Measured or Reasonably Estimated Shallow Soil Gas Concentration [if available]	Target Dee Concer Correspondii Indoor Air Co Where the Indoor Air A Factor Cook	ntration ing to Target concentration Soil Gas to Attenuation =0.01	Measured or Reasonably Estimated Deep Soil Gas Concentration [if available]	Target Groundwater Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor = 0.001 and Partitioning Across the Water Table Obeys Henry's Law C _{ge}	Measured or Reasonably Estimated Groundwater Concentration [if available]
100000	Acenaphthene	Sources	NC=noncancer risk	(ug/m³)	(ppbv)	(specify units)	(ug/m³)	(ppbv)	(specify units)	(ug/m³)	(ppbv)	(specify units)	(ug/L)	(specify units)		
	Acetaldehyde	1 ^	NC NC	2.1E+02	3.3E+01		2.1E+03	3.3E+02		2.1E+04	3.3E+03		••	-		
- 100	Acetone	×	NC NC	9.0E+00 3.5E+02	5.0E+00		9.0E+01	5.0E+01		9.0E+02	5.0E+02		2.8E+03			
	Acetonitrile	1 ^	NC NC	6.0E+01	1.5E+02 3.6E+01		3.5E+03 6.0E+02	1.5E+03 3.6E+02		3.5E+04	1.5E+04		2.2E+05			
120000	Acetophenone	×	NC NC	3.5E+02	7.1E+01		3.5E+03	7.1E+02		6.0E+03	3.6E+03		4.2E+04			
	Acrolein		NC NC	2.0E-02	8.7E-03		3.5E+03 2.0E-01	70.000.000		3.5E+04	7.1E+03		8.0E+05			
5 20 10 20 4	Acrylonitrile		NC NC	2.0E+00	9.2E-01		2.0E+01	8.7E-02 9.2E+00		2.0E+00	8.7E-01		4.0E+00			
309002			C	5.0E-02	3.3E-03		5.0E-01			2.0E+02	9.2E+01		4.7E+02			
	alpha-HCH (alpha-BHC)		С	1.4E-01	1.1E-02		1.4E+00	3.3E-02 1.1E-01		5.0E+00	3.3E-01		7.1E+00			
Same No.	Benzaldehyde	x	NC NC	3.5E+02	8.1E+01					1.4E+01	1.1E+00		3.1E+02			
	Benzene	^	C	3.1E+01	9.8E+00		3.5E+03	8.1E+02		3.5E+04	8.1E+03		3.6E+05			
100	Benzo(b)fluoranthene	×	c	1.2E+00	1.1E-01		3.1E+02	9.8E+01		3.1E+03	9.8E+02		1.4E+02			
	Benzylchloride	x	c	5.0E+00	9.7E-01		5.0E+01	9.7E+00		5.0E+02	9.7E+01					
	beta-Chloronaphthalene	x	NC	2.8E+02	4.2E+01		2.8E+03	4.2E+02		2.8E+04	4.2E+03		3.0E+02			
	Biphenyl	×	NC	1.8E+02	2.8E+01		1.8E+03	2.8E+02		1.8E+04	2.8E+03					
	Bis(2-chloroethyl)ether		С	7.4E-01	1.3E-01		7.4E+00	1.3E+00		7.4E+01	1.3E+01					
10000000000	Bis(2-chloroisopropyl)ether		c	2.4E+01	3.5E+00		2.4E+02	3.5E+01	-	2.4E+03	3.5E+02		1.0E+03			
	Bis(chloromethyl)ether		C	3.9E-03	8.4E-04	-	3.9E-02	8.4E-03		S. Samuel March	Carried Street		5.1E+03			
	Bromodichloromethane	×	c	1.4E+01	2.1E+00		1.4E+02	2.1E+01		3.9E-01 1.4E+03	8.4E-02 2.1E+02		4.5E-01			
	Bromoform	1	c	2.2E+02	2.1E+01		2.2E+03	2.1E+01			Samuelan.		2.1E+02			
1.00	1,3-Butadiene		c	8.7E-01	3.9E-01		8.7E+00	3.9E+00		2.2E+04 8.7E+01	2.1E+03 3.9E+01		8.3E-01			
	Carbon disulfide		NC	7.0E+02	2.2E+02		7.0E+03	2.2E+03		7.0E+04	2.2E+04		2.9E-01 5.6E+02			
	Carbon tetrachloride		C	1.6E+01	2.6E+00		1.6E+02	2.6E+01		1.6E+03	2.6E+02		1.3E+01			
	Chlordane		NC	7.0E-01	4.2E-02		7.0E+00	4.2E-01		7.0E+01	4.2E+00		1.36+01			
	2-Chloro-1,3-butadiene (chloroprene)		NC	7.0E+00	1.9E+00		7.0E+00 7.0E+01	1.9E+01		7.0E+01 7.0E+02			1.4E+01			
	Chlorobenzene	1	NC NC	6.0E+01	1.3E+01		6.0E+02	1.9E+01		6.0E+03	1.9E+02 1.3E+03		3.9E+02			
	1-Chlorobutane	×	NC NC	1.4E+03	3.7E+02		1.4E+04	3.7E+03		1.4E+05	3.7E+04		3.9E+02 2.0E+03			
7	Chlorodibromomethane	x	C	1.4E+03	1.2E+00		1.4E+04 1.0E+02	1.2E+01								
	Chlorodifluoromethane	1	NC	5.0E+04	1.4E+04		5.0E+05	1.4E+05		1.0E+03	1.2E+02		3.2E+02			
							-									
	Chloroethane (ethyl chloride)	1	NC	1.0E+04	3.8E+03	-	1.0E+05	3.8E+04		1.0E+06	3.8E+05	-	2.8E+04	-		
	Chloroform	-	С	1.1E+01	2.2E+00		1.1E+02	2.2E+01		1.1E+03	2.2E+02		8.0E+01 [†]			
	2-Chlorophenol	×	NC	1.8E+01	3.3E+00	-	1.8E+02	3.3E+01		1.8E+03	3.3E+02	-	1.1E+03			
	2-Chloropropane	1	NC .	1.0E+02	3.2E+01		1.0E+03	3.2E+02		1.0E+04	3.2E+03		1.7E+02			
	Chrysene	X	200.0											1200.		
	cis-1,2-Dichloroethylene	X	NC	3.5E+01	8.8E+00		3.5E+02	8.8E+01		3.5E+03	8.8E+02		2.1E+02	1,200 M		
123739	Crotonaldehyde (2-butenal)	X	C NC	4.5E-01 4.0E+02	1.6E-01 8.1E+01		4.5E+00 4.0E+03	1.6E+00 8.1E+02		4.5E+01 4.0E+04	1.6E+01 8.1E+03		5.6E+02 8.4E+00	-		

(total DCE)

Table 2a: Question 4 Generic Screening Levels and Summary Sheet ¹ Risk = 1 x 10⁻⁴

CAS No.		Compounds with Provisional Toxicity Data Extrapolated From Oral Sources	Basis of Target Concentration C=cancer risk NC=noncancer risk	Target Indoor Air Concentration to Salisty Both the Prescribed Risk Level and the Target Hazard Index [R=10.4, Hi=1) Cotempt (ug/m) (ppbv)		Measured or Reasonably Estimated Indoor Air Concentration [if available] (specify units)	Target Shallow Soll Gas Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor=0.1 Cooleges (up/m³) (ppbv)		Measured or Reasonably Estimated Shallow Soil Gas Concentration [if available] (specify units)	Target Deep Soil Gas Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor=0.01 Coologs (ug/m³) (ppbv)		Measured or Reasonably Estimated Deep Soil Gas Concentration [if available] (specify units)	Target Groundwater Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor = 0.001 and Partitioning Across the Water Table Obeys Henry's Law Cope (ug/L)	Measured or Reasonably Estimated Groundwater Concentration [if available] (specify units)
72559	Chemical	X	С	2.5E+00	(ppbv) 1.9E-01	(specify units)	2.5E+01	1.9E+00	(apeciny drina)	**	**	(opcour) armoy		
	Dibenzofuran	x	NC	1.4E+01	2.0E+00		1.4E+02	2.0E+01		1.4E+03	2.0E+02			
	1,2-Dibromo-3-chloropropane	1	NC	2.0E-01	2.1E-02		2.0E+00	2.1E-01		2.0E+01	2.1E+00		3.3E+01	
	1,2-Dibromoethane (ethylene dibromide)		NC	2.0E-01	2.6E-02		2.0E+00	2.6E-01		2.0E+01	2.6E+00		6.6E+00	
	1,3-Dichlorobenzene	×	NC	1.1E+02	1.7E+01		1.1E+03	1.7E+02		1.1E+04	1.7E+03		8.3E+02	
20000	1,2-Dichlorobenzene	-	NC	2.0E+02	3.3E+01		2.0E+03	3.3E+02		2.0E+04	3.3E+03		2.6E+03	
	1.4-Dichlorobenzene		NC	8.0E+02	1.3E+02		8.0E+03	1.3E+03		8.0E+04	1.3E+04		8.2E+03	
	Dichlorodifluoromethane		NC	2.0E+02	4.0E+01		2.0E+03	4.0E+02		2.0E+04	4.0E+03		1.4E+01	
	1,1-Dichloroethane		NC	5.0E+02	1.2E+02		5.0E+03	1.2E+03		5.0E+04	1.2E+04		2.2E+03	
700000000000000000000000000000000000000	1,2-Dichloroethane		C	9.4E+00	2.3E+00		9.4E+01	2.3E+01		9.4E+02	2.3E+02		2.3E+02	
			NC	2.0E+02	5.0E+01		2.0E+03	5.0E+02		2.0E+04	5.0E+03		1.9E+02	8 49/
	1,1-Dichloroethylene		NC NC	4.0E+00	8.7E-01		4.0E+01	8.7E+00		4.0E+02	8.7E+01		3.5E+01	18
W130000	1,2-Dichloropropane		NC NC	2.0E+01	4.4E+00		2.0E+02	4.4E+01		2.0E+03	4.4E+02		2.8E+01	
	1,3-Dichloropropene	1	C	5.3E-02	3.4E-03		5.3E-01	3.4E-02		5.3E+00	3.4E-01		8.6E+01	
	Dieldrin	×	NC	2.1E+01	1.3E+00		2.1E+02	1.3E+01						
	Endosulfan	† ^ -	NC NC	1.0E+00	2.6E-01		1.0E+01	2.6E+00		1.0E+02	2.6E+01		8.0E+02	
C. C	Epichlorohydrin	×	NC NC	7.0E+02	2.3E+02		7.0E+03	2.3E+03		7.0E+04	2.3E+04		5.2E+02	
	Ethyl ether	x	NC NC	3.2E+03	8.7E+02		3.2E+04	8.7E+03		3.2E+05	8.7E+04		5.6E+05	
5000000	Ethylacetate	_ ^	C	2.2E+02	5.1E+01	-	2.2E+03	5.1E+02		2.2E+04	5.1E+03		7.0E+02 [†]	
	Ethylbenzene				1.4E+00		2.4E+01	1.4E+01		2.4E+02	1.4E+02		1.1E+02	
14000	Ethylene oxide		C	2.4E+00	6.8E+01		3.2E+03	6.8E+02		3.2E+04	6.8E+03		9.1E+03	
Concession of	Ethylmethacrylate	X	NC NC	3.2E+02	2.1E+01		1.4E+03	2.1E+02			••			
	Fluorene	X	NC NC	1.4E+02	100000000		3.5E+01	1.3E+01		3.5E+02	1.3E+02		1.6E+01	
110009	military and at the contract of the	X	NC	3.5E+00	1.3E+00		6.6E+00	5.5E-01		6.6E+01	5.5E+00		1.1E+03	
	gamma-HCH (Lindane)	X	С	6.6E-01	5.5E-02		1.9E+00	1.2E-01		1.9E+01	1.2E+00		4.0E-01 [†]	
	Heptachlor	-	С	1.9E-01	1.2E-02		1.1E+02	1.0E+01		1.1E+03	1.0E+02		3.3E+01	
	Hexachloro-1,3-butadiene	-	С	1.1E+01	1.0E+00 4.5E-02		5.3E+00	4.5E-01		5.3E+01	4.5E+00			
10130000	Hexachlorobenzene	+	С	5.3E-01				1.8E-01		2.0E+01	1.8E+00		5.0E+01 [†]	
	Hexachlorocyclopentadiene	-	NC	2.0E-01	1.8E-02		2.0E+00	6.3E+01		6.1E+03	6.3E+02		3.8E+02	
	Hexachloroethane	1	C	6.1E+01	6.3E+00		6.1E+02	5.7E+02		2.0E+04	5.7E+03		2.9E+00	
	Hexane	-	NC	2.0E+02	5.7E+01		2.0E+03	2.7E+01		3.0E+02	2.7E+02		5.5E+02	
	Hydrogen cyanide		NC	3.0E+00	2.7E+00		3.0E+01	3.5E+03		1.1E+05	3.5E+04		2.2E+06	
Samuel Control	Isobutanol	X	NC	1.1E+03	3.5E+02		1.1E+04			3.0E+01	3.7E+00		6.8E-01	
	Mercury (elemental)	-	NC	3.0E-01	3.7E-02	-	3.0E+00	3.7E-01		7.0E+01	2.6E+01		6.9E+01	
	Methacrylonitrile	-	NC	7.0E-01	2.6E-01	-	7.0E+00	2.6E+00		7.0E+01	2.6E+01		**	
72435	Methoxychlor	X	NC	1.8E+01	1.2E+00	-				3.5E+05	1.2E+05		7.2E+05	
79209	Methyl acetate	X	NC NC	3.5E+03 1.1E+02	1.2E+03 3.0E+01		3.5E+04 1.1E+03	1.2E+04 3.0E+02		1.1E+04	3.0E+03		1.4E+04	

Table 2a: Question 4 Generic Screening Levels and Summary Sheet ¹ Risk = 1 x 10 ⁴

CAS No.	Chemical	Compounds with Provisional Toxicity Data Extrapolated From Oral Sources	Basis of Target Concentration C=cancer risk NC=noncancer risk	Target Indic Concentration Both the Presc Level and the Ta Index [R=10 ⁻⁴ , I) C _{target} (ug/m ³)	to Satisfy ribed Risk rget Hazard (tl=1)	Indoor Air Concentration [if available]	Target Shallov Concentration Co to Target In Concentration W Gas to Indoor Air Factor= C _{soling}	orresponding door Air here the Soil Attenuation 0.1	Estimated Shallow Soil Gas Concentration [if available]	Target Dee Concen Correspondir Indoor Air Co Where the S Indoor Air A Factor	tration ing to Target oncentration Soil Gas to uttenuation =0.01	Measured or Reasonably Estimated Deep Soil Gas Concentration [if available]	Target Groundwater Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor = 0.001 and Paritiboring Across the Water Table Obeys Henry's Law Cope	Measured or Reasonably Estimated Groundwater Concentration [if available]
	Methyl bromide	Sources		- TOO 200 000 000 000 000 000 000 000 000 0	(ppbv)	(specify units)	(ug/m³)	(ppbv)	(specify units)	(ug/m³)	(ppbv)	(specify units)	(ug/L)	(specify units
	Methyl chloride (chloromethane)		NC NC	5.0E+00	1.3E+00		5.0E+01	1.3E+01		5.0E+02	1.3E+02		2.0E+01	
	Methylcyclohexane	1	NC NC	9.0E+01	4.4E+01		9.0E+02	4.4E+02		9.0E+03	4.4E+03		2.5E+02	
	Methylene bromide	x	NC NC	3.0E+03	7.5E+02		3.0E+04	7.5E+03		3.0E+05	7.5E+04		7.1E+02	
CONTROL	Methylene chloride	-		3.5E+01	4.9E+00		3.5E+02	4.9E+01		3.5E+03	4.9E+02		9.9E+02	
7			С	5.2E+02	1.5E+02		5.2E+03	1.5E+03		5.2E+04	1.5E+04		5.8E+03	
	Methylethylketone (2-butanone)		NC	1.0E+03	3.4E+02		1.0E+04	3.4E+03		1.0E+05	3.4E+04	-	4.4E+05	
	Methylisobutylketone	-	NC	8.0E+01	2.0E+01	-	8.0E+02	2.0E+02		8.0E+03	2.0E+03		1.4E+04	
	Methylmethacrylate	-	NC	7.0E+02	1.7E+02		7.0E+03	1.7E+03		7.0E+04	1.7E+04		5.1E+04	
Service and	2-Methylnaphthalene	X	NC	7.0E+01	1.2E+01		7.0E+02	1.2E+02		7.0E+03	1.2E+03		3.3E+03	
1634044	MTBE		NC	3.0E+03	8.3E+02		3.0E+04	8.3E+03		3.0E+05	8.3E+04		1.2E+05	
108383	m-Xylene	×	NC	7.0E+03	1.6E+03		7.0E+04	1.6E+04		7.0E+05	1.6E+05		2.3E+04	
91203	Naphthalene		NC	3.0E+00	5.7E-01		3.0E+01	5.7E+00		3.0E+02	5.7E+01		1.5E+02	
104518	n-Butylbenzene	x	NC	1.4E+02	2.6E+01		1.4E+03	2.6E+02		1.4E+04	2.6E+03		2.6E+02	
98953	Nitrobenzene		NC	2.0E+00	4.0E-01		2.0E+01	4.0E+00		2.0E+02	4.0E+01		2.0E+03	
79469	2-Nitropropane		С	9.0E-02	2.5E-02		9.0E-01	2.5E-01		9.0E+00	2.5E+00		1.8E+01	
924163	N-Nitroso-di-n-butylamine		С	1.5E-01	2.4E-02		1.5E+00	2.4E-01		1.5E+01	2.4E+00		1.2E+01	
103651	n-Propylbenzene	x	NC	1.4E+02	2.8E+01		1.4E+03	2.8E+02		1.4E+04	2.8E+03		3.2E+02	
88722	o-Nitrotoluene	×	NC	3.5E+01	6.2E+00		3.5E+02	6.2E+01		3.5E+03	6.2E+02		6.8E+04	
95476	o-Xylene	×	NC	7.0E+03	1.6E+03		7.0E+04	1.6E+04		7.0E+05	1.6E+05		3.3E+04	
	p-Xylene	×	NC	7.0E+03	1.6E+03	200	7.0E+04	1.6E+04		7.0E+05	1.6E+05		2.2E+04	
	Pyrene	x	NC	1.1E+02	1.3E+01			**			**		**	
	sec-Butylbenzene	×	NC	1.4E+02	2.6E+01		1.4E+03	2.6E+02		1.4E+04	2.6E+03		2.5E+02	
	Styrene	1 ^	NC	1.0E+03	2.3E+02		1.0E+04	2.3E+03		1.0E+05	2.3E+04	-	8.9E+03	
- SEATOR	a little a respective from	×	NC NC	1.4E+02	2.6E+01		1.4E+03	2.6E+02		1.4E+04	2.6E+03	1	2.9E+02	
	tert-Butylbenzene	1 ^	C	3.3E+01	4.8E+00		3.3E+02	4.8E+01		3.3E+03	4.8E+02		3.3E+02	
	1,1,1,2-Tetrachioroethane			12.63.50.53	100000		1 0.000000000			1 Salaway (1955)	Section Assess		3.3E+02 3.0E+02	
	1,1,2,2-Tetrachloroethane	1	С	4.2E+00	6.1E-01		4.2E+01	6.1E+00		4.2E+02	6.1E+01			
	Tetrachloroethylene	-	С	8.1E+01	1.2E+01		8.1E+02	1.2E+02		8.1E+03	1.2E+03		1.1E+02	TO SEE STATE OF THE SECOND
	Toluene		NC	4.0E+02	1.1E+02		4.0E+03	1.1E+03		4.0E+04	1.1E+04		1.5E+03	56.
	trans-1,2-Dichloroethylene	X	NC	7.0E+01	1.8E+01		7.0E+02	1.8E+02		7.0E+03	1.8E+03	-	1.8E+02	56 ug
76131		-	NC	3.0E+04	3.9E+03		3.0E+05	3.9E+04		3.0E+06	3.9E+05		1.5E+03	U
	1,2,4-Trichlorobenzene		NC	2.0E+02	2.7E+01		2.0E+03	2.7E+02		2.0E+04	2.7E+03	-	3.4E+03	
79005	1,1,2-Trichloroethane		С	1.5E+01	2.8E+00		1.5E+02	2.8E+01		1.5E+03	2.8E+02		4.1E+02	
71556	1,1,1-Trichloroethane		NC	2.2E+03	4.0E+02		2.2E+04	4.0E+03	-	2.2E+05	4.0E+04		3.1E+03	.
79016	Trichloroethylene ***	X	С	2.2E+00	4.1E-01		2.2E+01	4.1E+00		2.2E+02	4.1E+01		5.3E+00.	72 Mg
75694	Trichlorofluoromethane		NC	7.0E+02	1.2E+02		7.0E+03	1.2E+03		7.0E+04	1.2E+04		1.8E+02	0
96184	1,2,3-Trichloropropane		NC	4.9E+00	8.1E-01		4.9E+01	8.1E+00		4.9E+02	8.1E+01		2.9E+02	
95636	1,2,4-Trimethylbenzene		NC	6.0E+00	1.2E+00		6.0E+01	1.2E+01		6.0E+02	1.2E+02		2.4E+01	

Table 2b: Question 4 Generic Screening Levels and Summary Sheet ¹ Risk = 1 x 10⁻⁵

CAS No. Chemica	Compounds with Provisional Toxicity Data Extrapolated From Oral Sources	Basis of Target Concentration C=cancer risk NC=noncancer risk	Target Indo Concentration Both the Presc Level and the Tale Index [R=10-5, t Ctarge (ug/m3)	to Satisfy ribed Risk rget Hazard (H=1)	Measured or Reasonably Estimated Indoor Air Concentration [if available] (specify units)	Target Shallon Concentration C to Target In Concentration W Gas to Indoor Ai Factor= C soil a (ug/m3)	orresponding door Air here the Soil r Attenuation 0.1	Measured or Reasonably Estimated Shallow Soil Gas Concentration [if available] (specify units)	Concer Correspondi Indoor Air Co	ng to Target oncentration Soil Gas to Attenuation =0.01	Measured or Reasonably Estimated Deep Soil Gas Concentration [if available] (specify units)	Target Groundwater Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor = 0.001 and Partitioning Across the Water Table Obeys Henry's Law Com (ug/L)	Measured or Reasonably Estimated Groundwater Concentration [if available] (specify units
83329 Acenaphthene	x	NC	2.1E+02	3.3E+01		2.1E+03	3.3E+02		2.1E+04	3.3E+03			
75070 Acetaldehyde		NC	9.0E+00	5.0E+00		9.0E+01	5.0E+01		9.0E+02	5.0E+02		2.8E+03	
67641 Acetone	x	NC	3.5E+02	1.5E+02		3.5E+03	1.5E+03		3.5E+04	1.5E+04		2.2E+05	
75058 Acetonitrile		NC	6.0E+01	3.6E+01		6.0E+02	3.6E+02		6.0E+03	3.6E+03		4.2E+04	
98862 Acetophenone	X	NC	3.5E+02	7.1E+01		3.5E+03	7.1E+02		3.5E+04	7.1E+03		8.0E+05	
107028 Acrolein		NC	2.0E-02	8.7E-03		2.0E-01	8.7E-02		2.0E+00	8.7E-01		4.0E+00	
107131 Acrylonitrile		С	3.6E-01	1.7E-01		3.6E+00	1.7E+00		3.6E+01	1.7E+01		8.5E+01	
309002 Aldrin		С	5.0E-03	3.3E-04		5.0E-02	3.3E-03		5.0E-01	3.3E-02		7.1E-01	
319846 alpha-HCH (alpha-BHC)		С	1.4E-02	1.1E-03		1.4E-01	1.1E-02		1.4E+00	1.1E-01		3.1E+01	
100527 Benzaldehyde	x	NC	3.5E+02	8.1E+01		3.5E+03	8.1E+02		3.5E+04	8.1E+03		3.6E+05	
71432 Benzene		С	3.1E+00	9.8E-01		3.1E+01	9.8E+00		3.1E+02	9.8E+01		1.4E+01	
205992 Benzo(b)fluoranthene	×	С	1.2E-01	1.1E-02		1.2E+00	1.1E-01						
100447 Benzylchloride	x	С	5.0E-01	9.7E-02		5.0E+00	9.7E-01		5.0E+01	9.7E+00		3.0E+01	
91587 beta-Chloronaphthalene	×	NC	2.8E+02	4.2E+01		2.8E+03	4.2E+02		2.8E+04	4.2E+03			
92524 Biphenyl	×	NC	1.8E+02	2.8E+01		1.8E+03	2.8E+02		1.8E+04	2.8E+03			
111444 Bis(2-chloroethyl)ether		С	7.4E-02	1.3E-02		7.4E-01	1.3E-01		7.4E+00	1.3E+00		1.0E+02	
108601 Bis(2-chloroisopropyl)ether		С	2.4E+00	3.5E-01		2.4E+01	3.5E+00		2.4E+02	3.5E+01		5.1E+02	
542881 Bis(chloromethyl)ether		С	3.9E-04	8.4E-05		3.9E-03	8.4E-04		3.9E-02	8.4E-03		4.5E-02	
75274 Bromodichloromethane	x	С	1.4E+00	2.1E-01		1.4E+01	2.1E+00		1.4E+02	2.1E+01		2.1E+01	
75252 Bromoform		С	2.2E+01	2.1E+00		2.2E+02	2.1E+01		2.2E+03	2.1E+02		8.3E-02	
106990 1,3-Butadiene		С	8.7E-02	3.9E-02		8.7E-01	3.9E-01		8.7E+00	3.9E+00		2.9E-02	
75150 Carbon disulfide		NC	7.0E+02	2.2E+02		7.0E+03	2.2E+03		7.0E+04	2.2E+04		5.6E+02	
56235 Carbon tetrachloride		C	1.6E+00	2.6E-01		1.6E+01	2.6E+00		1.6E+02	2.6E+01		5.0E+00 [†]	
57749 Chlordane		С	2.4E-01	1.5E-02		2.4E+00	1.5E-01		2.4E+01	1.5E+00		.,	
126998 2-Chloro-1,3-butadiene (ch	loroprepe)	NC	7.0E+00	1.9E+00		7.0E+01	1.9E+01		7.0E+02	1.9E+02		1.4E+01	
108907 Chlorobenzene	loroprene)	NC	6.0E+01	1.3E+01		6.0E+02	1.3E+02		6.0E+03	1.3E+03		3.9E+02	
109693 1-Chlorobutane	x	NC NC	1.4E+03	3.7E+02		1.4E+04	3.7E+03		1.4E+05	3.7E+04		2.0E+03	
124481 Chlorodibromomethane	x	C	1.0E+00	1.2E-01		1.0E+01	1.2E+00		1.0E+02	1.2E+01		3.2E+01	
75456 Chlorodifluoromethane	^	NC NC	5.0E+04	1.4E+04		5.0E+05	1.4E+05		**			**	
75003 Chloroethane (ethyl chlorid	0)	NC NC	1.0E+04	3.8E+03		1.0E+05	3.8E+04		1.0E+06	3.8E+05		2.8E+04	
	0)	C	1.0E+04 1.1E+00	3.8E+03		1.0E+05 1.1E+01	2.2E+00		1.1E+02	2.2E+01		8.0E+01 [†]	
67663 Chloroform 95578 2-Chlorophenol	×	NC NC	1.1E+00 1.8E+01	3.3E+00		1.1E+01 1.8E+02	3.3E+01		1.1E+02 1.8E+03	3.3E+02		1.1E+03	77
	x		1.8E+01 1.0E+02	3.3E+00 3.2E+01		1.8E+02 1.0E+03	3.3E+01 3.2E+02		1.8E+03	3.3E+02 3.2E+03		1.7E+02	
75296 2-Chloropropane	×	NC C	1.0E+02 1.2E+01	3.2E+01		1.0E+03	3.2E+02		1.0E+04	3.2E+03		1.7E+02	
218019 Chrysene										8.8E+02		2.1E+02	
156592 cis-1,2-Dichloroethylene	X	NC	3.5E+01	8.8E+00		3.5E+02	8.8E+01		3.5E+03			5.6E+01	
123739 Crotonaldehyde (2-butenal 98828 Cumene) X	C NC	4.5E-02 4.0E+02	1.6E-02 8.1E+01		4.5E-01 4.0E+03	1.6E-01 8.1E+02		4.5E+00 4.0E+04	1.6E+00 8.1E+03		8.4E+00	

Table 2a: Question 4 Generic Screening Levels and Summary Sheet 1

		Compounds with Provisional Toxicity Data Extrapolated From Oral	Basis of Target Concentration C=cancer risk	Target Inde Concentration Both the Presc Level and the Ta Inde: [R=10 ⁴ , I	to Satisfy ribed Risk rget Hazard (H=1)	Measured or Reasonably Estimated Indoor Air Concentration [if available]	Target Shallov Concentration Concentration W Gas to Indoor Ai Factor= C _{solio}	orresponding door Air here the Soil r Attenuation :0.1	Measured or Reasonably Estimated Shallow Soil Gas Concentration [if available]	Target Dee Concen Correspondii Indoor Air Co Where the S Indoor Air A Factor C ₅₀₀	ntration ng to Target oncentration Soil Gas to Attenuation =0.01	Measured or Reasonably Estimated Deep Soil Gas Concentration [if available]	Target Groundwater Concentration Corresponding to Target Indoor Air Concentration Where the Soil Gas to Indoor Air Attenuation Factor = 0.001 and Partitioning Across the Water Table Obeys Henry's Law Comment of the Comme	Measured or Reasonably Estimated Groundwater Concentration [if available]
CAS No.	Chemical	Sources	NC=noncancer risk	(ug/m³)	(ppbv)	(specify units)	(ug/m³)	(ppbv)	(specify units)	(ug/m³)	(ppbv)	(specify units)	(ug/L)	(specify units)
108678	1,3,5-Trimethylbenzene		NC	6.0E+00	1.2E+00		6.0E+01	1.2E+01	turi periodi	6.0E+02	1.2E+02		2.5E+01	
108054	Vinyl acetate		NC	2.0E+02	5.7E+01		2.0E+03	5.7E+02		2.0E+04	5.7E+03		9.6E+03	
75014	Vinyl chloride (chloroethene)		С	2.8E+01	1.1E+01		2.8E+02	1.1E+02		2.8E+03	1.1E+03		2.5E+01	200 49/

<sup>The Fig. 1 for Shallow Soil Gas Target Concentration

AF = 0.01 for Deep Soil Gas Target Concentration

AF = 0.01 for Deep Soil Gas Target Concentration

AF = 0.001 for Groundwater Target Concentration

Health-based target breathing concentration exceeds maximum possible chemical vapor concentration (pathway incomplete)</sup>

^{**} Target soil gas concentration exceeds maximum possible vapor concentration (pathway incomplete)

[†] The target groundwater concentration is the MCL. (The MCL for chioroform is the MCL for total Trihalomethanes. The MCL listed for rm-Xylene, o-Xylene, and p-Xylene is the MCL for total Xylenes.)

^{††} The target concentration for trichloroethylene is based on the upper bound cancer slope factor identified in EPA's draft risk assessment for trichloroethylene (US EPA, 2001). The slope factor is based on state-of-the-art methodology, however the TCE assessment is still undergoing review. As a result, the slope factor and the target concentration values for TCE may be revised further. (See Appendix D.)

APPENDIX B JOHNSON-ETTINGER MODELS FOR COLLIS FACILITY

DATA ENTRY SHEET Collis cis-1,2-DCE

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

		V=0	dwater conc. below)	
		YES	X	
	ENTER	ENTER Initial		
	Chemical	groundwater		
	CAS No.	conc.,		
	(numbers only,	Cw		
	no dashes)	(μg/L)	Ch	nemical
I	156592	1.20E+03	cis-1,2-Did	chloroethylene
RE	ENTER Depth	ENTER	ENTER	ENTER
	below grade			Average
	to bottom	Depth		soil/
	of enclosed	below grade	SCS	groundwater
	space floor,	to water table,	soil type	temperature,
	Le	Lwr	directly above	Ts
	(15 or 200 cm)	(cm)	water table	(°C)

YES

MORE ↓						
	ENTER Vadose zone		ENTER User-defined	ENTER	ENTER	ENTER
	SCS soil type		vadose zone soil vapor	Vadose zone soil dry	Vadose zone soil total	Vadose zone soil water-filled
	(used to estimate	OR	permeability,	bulk density,	porosity,	porosity,
	soil vapor permeability)		k _v (cm²)	ρ _ь ^V (g/cm³)	n ^v (unitless)	θ _w ^V (cm³/cm³)
	LS			1.5	0.43	0.3

_	ENTER Target risk for carcinogens, TR (unitless) 1.0E-06	Target hazard quotient for noncarcinogens, THQ (unitless)	Averaging time for carcinogens, AT _c (yrs)	ENTER Averaging time for noncarcinogens, AT _{NC} (yrs)	EXPOSURE duration, ED (yrs)	ENTER Exposure frequency EF (days/yr)	
F	1.0E-06	1	70	30	25	250	

RESULTS SHEET Collis cis-1,2-DCE Industrial

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

INCREMENTAL RISK CALCULATIONS:

Indoor	Indoor	Risk-based	Pure	Final
exposure	exposure	indoor	component	indoor
groundwater	groundwater	exposure	water	exposure
conc.,	conc.,	groundwater	solubility,	groundwater
carcinogen	noncarcinogen	conc.,	S	conc.,
(μg/L)	(μg/L)	(μg/L)	(μ g/L)	(μg/L)

Incremental	Hazard
risk from	quotient
vapor	from vapor
intrusion to	intrusion to
indoor air,	indoor air,
carcinogen	noncarcinogen
(unitless)	(unitless)
NA	9.9E-02

1

MESSAGE SUMMARY BELOW:

MESSAGE: Risk/HQ or risk-based groundwater concentration is based on a route-to-route extrapolation.

END

DATA ENTRY SHEET Collis TCE

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

	(enter "X" in "YES" bo	YES	X	
	ENTER	ENTER Initial		
	Chemical	groundwater		
	CAS No.	conc.,		
	(numbers only,	Cw		
	no dashes)	(μg/L)	Ch	nemical
	79016	9.20E+01	Trichlo	proethylene
IORE	ENTER Depth	ENTER	ENTER	ENTER
+	below grade			Average
	to bottom	Depth		soil/
	of enclosed	below grade	SCS	groundwater
	space floor,	to water table,	soil type	temperature,
	Le	Lwr	directly above	Ts

MORE ↓]					
	ENTER Vadose zone SCS soil type (used to estimate	OR	ENTER User-defined vadose zone soil vapor permeability,	ENTER Vadose zone soil dry bulk density,	ENTER Vadose zone soil total porosity,	ENTER Vadose zone soil water-filled porosity,
	soil vapor permeability)		k _v (cm²)	ρ _b ^V (g/cm ³)	n ^v (unitless)	θ _w ^V (cm³/cm³)
	LS			1.5	0.43	0.3

<u>.</u>	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)	ENTER Averaging time for carcinogens, ATc (yrs)	ENTER Averaging time for noncarcinogens, AT _{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency EF (days/yr)
F	1.0E-06	1	70	30	25	250

RESULTS SHEET Collis TCE

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

INCREMENTAL RISK CALCULATIONS:

Indoor	Indoor	Risk-based indoor exposure groundwater conc., (µg/L)	Pure	Final
exposure	exposure		component	indoor
groundwater	groundwater		water	exposure
conc.,	conc.,		solubility,	groundwater
carcinogen	noncarcinogen		S	conc.,
(µg/L)	(µg/L)		(µg/L)	(µg/L)
NA	l NA	NA	1.10E+06	NA

Hazard
quotient
from vapor
intrusion to
indoor air,
noncarcinogen
(unitless)
I NA

]

MESSAGE SUMMARY BELOW:

END

DATA ENTRY SHEET Collis VC

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

Conto	X 111 120 D	YES	dwater conc. below)	
	ENTER	ENTER Initial		
,	Chemical	groundwater		
	CAS No.	conc.,		
(nu	imbers only,	Cw		
n	o dashes)	(μg/L)	Ch	nemical
- 1	75014	2.00E+02	Vinyl chlorid	e (chloroethene)
 RE	ENTER	2.00E+02 ENTER	ENTER	e (chloroethene) ENTER
700				
b	ENTER Depth elow grade to bottom		ENTER	ENTER
b	ENTER Depth elow grade to bottom f enclosed	ENTER Depth below grade	ENTER	ENTER Average soil/ groundwater
b	ENTER Depth elow grade to bottom	ENTER Depth	ENTER	ENTER Average soil/
b	ENTER Depth elow grade to bottom f enclosed	ENTER Depth below grade	ENTER	ENTER Average soil/ groundwater

MORE .						
	ENTER Vadose zone SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined vadose zone soil vapor permeability, k _v (cm ²)	ENTER Vadose zone soil dry bulk density, Pb (g/cm³)	ENTER Vadose zone soil total porosity, n ^V (unitless)	ENTER Vadose zone soil water-filled porosity, θ_{w}^{V} (cm³/cm³)
	LS			1.5	0.43	0.3

	carcinogens, TR (unitless)	noncarcinogens, THQ (unitless)	time for carcinogens, AT _c (yrs)	time for noncarcinogens, AT _{NC} (yrs)	Exposure duration, ED (yrs)	frequency FF (days/yr)
F	1.0E-06	1	70	30	25	250

RESULTS SHEET Collis VC

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

INCREMENTAL RISK CALCULATIONS:

Indoor	Indoor	Risk-based	Pure	Final indoor exposure groundwater conc., (µg/L)
exposure	exposure	indoor	component	
groundwater	groundwater	exposure	water	
conc.,	conc.,	groundwater	solubility,	
carcinogen	noncarcinogen	conc.,	S	
(µg/L)	(µg/L)	(µg/L)	(µg/L)	
NA	l NA	NA NA	2.76F+06	NA

	Incremental	Hazard
	risk from	quotient
	vapor	from vapor
	intrusion to	intrusion to
	indoor air,	indoor air,
	carcinogen	noncarcinogen
	(unitless)	(unitless)
_	1 15 05	F 7F 00

]

MESSAGE SUMMARY BELOW:

END

APPENDIX C WELLS WITHIN 1 MILE OF COLLIS FACILITY

Owner	Well Number	Total Depth	Туре	Distance from Facility
COLLIS CORP.	7711	39	Monitoring	0
COLLIS CORP.	7713	17	Monitoring	0
COLLIS CORP.	7744	69	Monitoring	0
COLLIS CORP.	13978	1,633	Commercial	0
CLINTON COUNTRY CLUB	37155	872	Irrigation	< 0.5
CLINTON, CITY OF	5220	2,202	Municipal	< 0.5
				18
WESTERN ICE CO.	30903	1,500	Commercial	< 0.75
SWIFT & COMPANY	853	1,253	Commercial	< 1
SETHNESS CORPORATION	17669	1,276	Commercial	< 1
CLINTON, CITY OF	17856	165	Municipal, Other	< 1